

# BORDER™ - INGROUND EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# BORDER™ - INGROUND EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

### Bezel

Stainless steel.

### Finish

Double powder coating polyester high resistant to UV and oxidation.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

### Drivers

HPF, electronic 120/277V.

### Rough-in housing

Thermoplastic.

### Diffuser

8mm/0.3" tempered glass.

### Gasket

Silicone.

### Reflectors

High purity aluminum.

### Cable entry

M20 cable gland for DIA 6-12mm/0.24-0.47" cables.

### Walk over

Static pressure load 500Kg/1100lbs.

### Mechanical

For in-ground or wall installation in poured concrete or brick.

## MOUNTING & OPTICS



Ext-Inground



Medium



# BORDER™ - INGROUND EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**8107228** 8107228

**8107230** 8107230

**8107232** 8107232

**8107234** 8107234

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. OPTIONS

**SC** Second Cable Entry

**DB** Dimming (0-10V, 10%)

### D. ROUGH-IN HOUSING (REQUIRED)

**RIH280** Rough-In Housing for 15"  
Luminaires

**RIH281** Rough-In Housing for 25"  
Luminaires

**RIH282** Rough-In Housing for 37"  
Luminaires

**RIH283** Rough-In Housing for 48.5"  
Luminaires

## TECHNICAL DATA

### LUMINAIRE

Code	<b>8107228</b>	<b>8107230</b>	<b>8107232</b>	<b>8107234</b>
Power (LED)	9W	18W	27W	36W
Distribution	Medium 24	Medium 24	Medium 24	Medium 24
Delivered lms	990	1980	2957	3959
Length (A)	15"	25"	37"	48.5"

## APPROVALS



# BORDER™ - INGROUND EXTERIOR

## DIMENSIONAL DIAGRAMS

