

# CUBO CL™ - CEILING & CANOPY EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# CUBO CL™ - CEILING & CANOPY EXTERIOR

## GENERAL SPECIFICATION

### Housing

Die-cast aluminum.

### External Screws

Stainless steel.

### Lens

6mm/0.25" tempered glass.

### Gaskets

One piece silicone.

### Finish

Silver powder coated RAL9006 or black powder coated.

### Drivers

HPF, electronic for 120-277V (EU-240V).

### Minimum Starting Temperature

-30°C for LEDs.

### Conduit entry

PG11 gland for 11mm/0.625" DIA cable.

### Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

## MOUNTING & OPTICS



Ext-Ceiling/Canopy

# CUBO CL™ - CEILING & CANOPY EXTERIOR

## HOW TO ORDER

### A. L

**810347** 810347

**810348** 810348

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**GR** Gray RAL 9006

### D. DIMMING

**DB** Dimming (0-10V, 10%)

## TECHNICAL DATA

### LUMINAIRE

Code	<b>810347</b>	<b>810348</b>
Power (LED)	14W	14W
Beam	8°	40°
Delivered lms	1049	1049

## APPROVALS



# CUBO CL™ - CEILING & CANOPY EXTERIOR

## DIMENSIONAL DIAGRAMS

