

CUBO CL™ - CEILING & CANOPY EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



CUBO CL™ - CEILING & CANOPY EXTERIOR

GENERAL SPECIFICATION

Housing

Die-cast aluminum.

External Screws

Stainless steel.

Lens

6mm/0.25" tempered glass.

Gaskets

One piece silicone.

Finish

Silver powder coated RAL9006 or black powder coated.

Drivers

HPF, electronic for 120-277V (EU-240V).

Minimum Starting Temperature

-30°C for LEDs.

Conduit entry

PG11 gland for 11mm/0.625" DIA cable.

Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Ext-Ceiling/Canopy



CUBO CL™ - CEILING & CANOPY EXTERIOR

HOW TO ORDER

A. L

810347 810347

810348 810348

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

GR Gray RAL 9006

D. DIMMING

DB Dimming (0-10V, 10%)

TECHNICAL DATA

LUMINAIRE

Code	810347	810348
Power (LED)	14W	14W
Beam	8°	40°
Delivered lms	1049	1049

APPROVALS



CUBO CL™ - CEILING & CANOPY EXTERIOR

DIMENSIONAL DIAGRAMS

