CYLINDER EX™

SHORT SPECIFICATION SHEET



FIXTURE TYPE

FIXTURE CODE

QUANTITIES

1 HOW TO ORDER

LUMINAIRE

CYXW Wall

CYXC Surface

CYXP Pendant [1]

Conduit mount is an option for wall and ceiling versions, consult factory.

[1] Pendant is stem mount only.

DIAMETER

DR04 4"

DR06 6"

Tiltable head available on 6" diameter only.

DIRECTION

DT1 Direct (10" housing) [1] [2]

DT2 Direct/Indirect (12"/14" housing) [3]

[1] Available for Wall, Ceiling, and Pendant (10" tall housing for Direct). [2] Wall mount "direct only" can be installed pointing up or down.
[3] Available for Wall mount only. Direct/Indirect 4" diameter will have a 12" tall housing & 6" diameter will have a 14" tall housing.

LIGHT SOURCE

DN01 LEDs / Multi-Array Optics [1]

DN02 COB / Reflector

* All data based on max output and nominal values. [1] Available for 6" diameter only.

CRI

CR00 Not required (For Amber Light)

CR80 CRI 80+

CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

CTA62 Amber (Turtle Friendly) [1]

[1] Available for 6" diameter with LEDs / Multi-Array Optics and 50° direct distribution.

DISTRIBUTION DIRECT

BAT2 Type II [1]

BAT3 Type III [1]

BAT4 Type IV [1]

BA03 3° [2]

BA15 15° [3] [4] [5]

BA30 30° [3] [4] [5]

BA50 50° [3] [4]

BA70 70° [3] [5]

[1] Available for 6" Direct (2000, 2500 and 3000 lumens), with LEDs / Multi-Array Optics distribution, not recommended for Indirect use.
[2] Available for 6" with LEDs / Multi-Array Optics distribution and Wall mount. There may be a +/- 250K variance in color temperature. The head is not adjustable. [3] Available for 6" with LEDs / Multi-Array Optics distribution. [4] Available for 6" with COB / Reflector.
[5] Available for 4" with COB / Reflector.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

DISTRIBUTION INDIRECT

BB00 Not required

BB03 3° [1]

BB15 15° [2 3 4]

BB30 30° [2 3 4]

BB50 50° [2 3]

BB70 70° [2 4]

[1] Available for 6" with LEDs, Indirect, and Wall version only. There may be a +/- 250K variance in color temperature. The head is not adjustable. [2] Available for 6" with LEDs / Multi-Array Optics distribution. [3] Available for 6" with COB / Reflector.
[4] Available for 4" with COB / Reflector.

LUMENS DIRECT

LMA0005 59 lms [1]

LMA0040 400 lms [2]

LMA0200 2000 lms

LMA0250 2500 lms

LMA0300 3000 lms

LMA0350 3500 lms [3]

LMA0400 4000 lms [4]

[1] Available for 3° Indirect distribution.

LUMENS INDIRECT

LMB0000 Not required

LMB0005 59 lms [1]

LMB0200 2000 lms

LMB0250 2500 lms

LMB0300 3000 lms

[1] Available for 3° Indirect distribution.

VOLTAGE

V1 120/277V

V2 240V [1]

[1] Not available in North America.

DIMMING

DA01 0-10V Dimming 1.0%

DA11 0-10V Dimming 1.0% - Arctic driver [1 3]

DA12 0-10V Dimming 1.0% - Desert driver [2 3]

DA21 DALI Dimming 1.0% [3]

[1] Capable of operating at -30°C (-22°F) to ambient temperature. [2] Capable of operating at +50°C (+122°F) ambient temperature.
[3] Consult factory.

MOUNTING BRACKET

MB0 Not required

MB1 Narrow - Full [1 2]

MB2 Narrow - Standard [1 2]

MB3 Classic - Standard [1 3]

* Mounting bracket finish to match fixture finish.
[1] Only available with Wall mount version. [2] The Wall Narrow version mounts to a 2" x 4" switch box (supplied by others).
[3] The Wall Classic version mounts to a 4" x 4" junction box (supplied by others).

CONDUIT MOUNT

CDM0 Not required

CDM1 Required [1]

[1] Deep mounting box for use with conduit installations. Requires field-supplied weatherproof junction box (by others). Only available with MB3 mounting bracket.

SUSPENSION TYPE

ST00 Not required

ST01 Rigid Stem Mount [1]

ST02 Swivel Stem Mount [1]

* Custom lengths available; consult factory for details.
[1] Only available with Pendent Mount.

SUSPENSION HEIGHT

SL00 Not required

SL03 3ft [1]

* Stems will always be Black Metallic Textured finished.
[1] Custom length available, consult factory.

FIXTURE FINISH

FA01 White - Textured

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA27 Wood grain - Light Cherry [1]

FA28 Wood grain - Dark Walnut [1]

FA30 Wood grain - White Oak [1]

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

[1] Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

BEZEL FINISH

FB01 White - Textured

FB02 Black Metallic - Textured

FB20 Silver Metallic - Textured

FB46 Charcoal Metallic - Textured

FB47 Bronze Metallic - Textured

Shatterproof lens available, consult factory.

CANOPY & STEM FINISH

FC00 Not required

FC01 White - Textured

FC02 Black Metallic - Textured

FC20 Silver Metallic - Textured

FC46 Charcoal Metallic - Textured

FC47 Bronze Metallic - Textured

© 2026 Beta-Calco Inc. Specifications are subject to change without notice