



CYLINDER EX™

SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 HOW TO ORDER

LUMINAIRE	DIAMETER	DIRECTION	LIGHT SOURCE
<p>CYXW Wall CYXC Ceiling CYXP Pendant ¹</p> <p>Conduit mount is an option for wall and ceiling versions, consult factory. ¹ Pendant is stem mount only.</p>	<p>DR04 4" DR06 6"</p> <p>Tilttable head available on 6" diameter only.</p>	<p>DT1 Direct (10" housing) ^{1 2} DT2 Direct/Indirect (12"/14" housing) ³</p> <p>¹ Available for Wall, Ceiling, and Pendant (10" tall housing for Direct). ² Wall mount "direct only" can be installed pointing up or down. ³ Available for Wall mount only. Direct/Indirect 4" diameter will have a 12" tall housing & 6" diameter will have a 14" tall housing.</p>	<p>DN01 LEDs / Multi-Array Optics ¹ DN02 COB / Reflector</p> <p>* All data based on max output and nominal values. ¹ Available for 6" diameter only.</p>
CRI	CCT	DISTRIBUTION DIRECT	
<p>CR00 Not required (For Amber Light) CR80 CRI 80+</p>	<p>CTA27 2700K CTA30 3000K CTA35 3500K CTA40 4000K CTA62 Amber (Turtle Friendly) ¹</p> <p>¹ Available for 6" diameter with LEDs / Multi-Array Optics and 50° direct distribution.</p>	<p>BAT2 Type II ¹ BAT3 Type III ¹ BAT4 Type IV ¹ BA03 3° ² BA15 15° ^{3 4 5} BA30 30° ^{3 4 5} BA50 50° ^{3 4} BA70 70° ^{3 5}</p> <p>¹ Available for 6" Direct (2000, 2500 and 3000 lumens), with LEDs / Multi-Array Optics distribution, not recommended for Indirect use. ² Available for 6" with LEDs / Multi-Array Optics distribution and Wall mount. There may be a +/- 250K variance in color temperature. The head is not adjustable. ³ Available for 6" with LEDs / Multi-Array Optics distribution. ⁴ Available for 6" with COB / Reflector. ⁵ Available for 4" with COB / Reflector.</p>	

<p>DISTRIBUTION INDIRECT</p> <p>BB00 Not required</p> <p>BB03 3°¹</p> <p>BB15 15°^{2 3 4}</p> <p>BB30 30°^{2 3 4}</p> <p>BB50 50°^{2 3}</p> <p>BB70 70°^{2 4}</p> <p>¹ Available for 6" with LEDs, Indirect, and Wall version only. There may be a +/- 250K variance in color temperature. The head is not adjustable. ² Available for 6" with LEDs / Multi-Array Optics distribution. ³ Available for 6" with COB / Reflector. ⁴ Available for 4" with COB / Reflector.</p>	<p>LUMENS DIRECT</p> <p>LMA0005 59 lms¹</p> <p>LMA0040 400 lms²</p> <p>LMA0200 2000 lms</p> <p>LMA0250 2500 lms</p> <p>LMA0300 3000 lms</p> <p>LMA0350 3500 lms³</p> <p>LMA0400 4000 lms⁴</p> <p>¹ Available for 3° Indirect distribution.</p>	<p>LUMENS INDIRECT</p> <p>LMB0000 Not required</p> <p>LMB0005 59 lms¹</p> <p>LMB0200 2000 lms</p> <p>LMB0250 2500 lms</p> <p>LMB0300 3000 lms</p> <p>¹ Available for 3° Indirect distribution.</p>	<p>VOLTAGE</p> <p>V1 120/277V</p> <p>V2 240V¹</p> <p>¹ Not available in North America.</p>
<p>DIMMING</p> <p>DA01 0-10V Dimming 1.0%</p> <p>DA11 0-10V Dimming 1.0% - Arctic driver^{1 3}</p> <p>DA12 0-10V Dimming 1.0% - Desert driver^{2 3}</p> <p>DA21 DALI Dimming 1.0%³</p> <p>¹ Capable of operating at -30°C (-22°F) to ambient temperature. ² Capable of operating at +50°C (+122°F) ambient temperature. ³ Consult factory.</p>	<p>MOUNTING BRACKET</p> <p>MBO Not required</p> <p>MB1 Narrow - Full^{1 2}</p> <p>MB2 Narrow - Standard^{1 2}</p> <p>MB3 Classic - Standard^{1 3}</p> <p>* Mounting bracket finish to match fixture finish.</p> <p>¹ Only available with Wall mount version. ² The Wall Narrow version mounts to a 2" x 4" switch box (supplied by others). ³ The Wall Classic version mounts to a 4" x 4" junction box (supplied by others).</p>	<p>CONDUIT MOUNT</p> <p>CDM0 Not required</p> <p>CDM1 Required¹</p> <p>¹ Deep mounting box for use with conduit installations. Requires field-supplied weatherproof junction box (by others). Only available with MB3 mounting bracket.</p>	<p>SUSPENSION TYPE</p> <p>ST00 Not required</p> <p>ST01 Rigid Stem Mount¹</p> <p>ST02 Swivel Stem Mount¹</p> <p>* Custom lengths available; consult factory for details. ¹ Only available with Pendant Mount.</p>
<p>SUSPENSION HEIGHT</p> <p>SL00 Not required</p> <p>SL03 3ft¹</p> <p>* Stems will always be Black Metallic Textured finished. ¹ Custom length available, consult factory.</p>	<p>FIXTURE FINISH</p> <p>FA01 White - Textured</p> <p>FA02 Black Metallic - Textured</p> <p>FA20 Silver Metallic - Textured</p> <p>FA27 Wood grain - Light Cherry¹</p> <p>FA28 Wood grain - Dark Walnut¹</p> <p>FA30 Wood grain - White Oak¹</p> <p>FA46 Charcoal Metallic - Textured</p> <p>FA47 Bronze Metallic - Textured</p> <p>¹ Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.</p>	<p>BEZEL FINISH</p> <p>FB01 White - Textured</p> <p>FB02 Black Metallic - Textured</p> <p>FB20 Silver Metallic - Textured</p> <p>FB46 Charcoal Metallic - Textured</p> <p>FB47 Bronze Metallic - Textured</p> <p>Shatterproof lens available, consult factory.</p>	<p>CANOPY & STEM FINISH</p> <p>FC00 Not required</p> <p>FC01 White - Textured</p> <p>FC02 Black Metallic - Textured</p> <p>FC20 Silver Metallic - Textured</p> <p>FC46 Charcoal Metallic - Textured</p> <p>FC47 Bronze Metallic - Textured</p>