

CYLINDRA™ - WALL SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



CYLINDRA™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum

Finish

Black plate, powder coated gloss white.

Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V (1.0%) dimming standard.

L70 @25°C (77°F)

> 50,000 hrs.

Finials

Cylindrical buttons (CB) are brushed stainless steel.

Lens

Opal acrylic with a sandblasted face.


Mechanical

Luminaire mounts directly to a junction box. Additional mounting positions also provided.

Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Wall

CYLINDRA™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

418100 418100

418200 418200

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

TECHNICAL DATA

LUMINAIRE

Code	418100	418200
Power	20W	40W
Delivered Ims	1100	2200
LPW	50	50
Height (A)	12"	24"

APPROVALS



IP20

CYLINDRA™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

