

# CYLINDRA™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# CYLINDRA™ - WALL SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum

### Finish

Black plate, powder coated gloss white.

### Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V (1.0%) dimming standard.

### L70 @25°C (77°F)

> 50,000 hrs.

### Finials

Cylindrical buttons (CB) are brushed stainless steel.

### Lens

Opal acrylic with a sandblasted face.


### Mechanical

Luminaire mounts directly to a junction box. Additional mounting positions also provided.

### Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Wall



# CYLINDRA™ - WALL SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**418100** 418100

**418200** 418200

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

## TECHNICAL DATA

### LUMINAIRE

Code	<b>418100</b>	<b>418200</b>
Power	20W	40W
Delivered lms	1100	2200
LPW	50	50
Height (A)	12"	24"

---

## APPROVALS

ADA



CE



IP20



# CYLINDRA™ - WALL SURFACE

## DIMENSIONAL DIAGRAMS

