

# ERELLA™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ERELLA™ - CEILING SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Lens

Opal polycarbonate.

### Luminaire orientation

Ceiling or wall mounted.

### Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

### Finish

Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

### Mechanical

Mounts directly to a junction box (by others - North America only).


### Approvals

Damp Location (Indoor use only).

## OPTICS & FEATURES



Ceiling



Direct



# ERELLA™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**600300** 18", 1898 lms

**600400** 23", 2078 lms

**600410** 23", 2745 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. LENS

**OP** Opal Acrylic

### D. FINISH

**WH** White

**BM** Bronze Metallic Textured

**MS** Silver Metallic

**AB** Antique Brass

**PB** Polished Brass

**SB** Satin Brass

**PC** Polished Chrome

**SN** Satin Nickel

**F39** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish (sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

| Code          | <b>600300</b> | <b>600400</b> | <b>600410</b> |
|---------------|---------------|---------------|---------------|
| Power (LED)   | 28W           | 28W           | 36W           |
| Delivered lms | 1898          | 2078          | 2745          |
| LPW           | 70            | 75            | 76            |
| Diameter (A)  | 18"           | 23"           | 23"           |
| Depth (D)     | 4"            | 4"            | 4"            |
| Weight        | 8.1lb         | 9.9lb         | 9.9lb         |

## APPROVALS



DAMP  
LOCATION



IP20



# ERELLA™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

