

# ERELLA™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



# ERELLA™ - CEILING SURFACE

## GENERAL SPECIFICATION

**Body and trim**

Steel and aluminum.

**Lens**

Opal polycarbonate.

**Luminaire orientation**

Ceiling or wall mounted.

**Delivered Lumens**

Delivered lumens and LPW based on 3000K (min 80 CRI).

**Finish**

Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

**Drivers**

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.


**Mechanical**

Mounts directly to a junction box (by others - North America only).

**Approvals**

Damp Location (Indoor use only).

## OPTICS & FEATURES



# ERELLA™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**600300** 18", 1898 lms                      **600400** 23", 2078 lms                      **600410** 23", 2745 lms

### B. CCT

**30** 3000K (min 80 CRI)                      **35** 3500K (min 80 CRI)                      **40** 4000K (min 80 CRI)

### C. LENS

**OP** Opal Acrylic

### D. FINISH

<b>WH</b> White	<b>BM</b> Bronze Metallic Textured	<b>MS</b> Silver Metallic	<b>AB</b> Antique Brass
<b>PB</b> Polished Brass	<b>SB</b> Satin Brass	<b>PC</b> Polished Chrome	<b>SN</b> Satin Nickel
<b>F39</b> Other painted finish (RAL number required)	<b>F40</b> Other Non-RAL painted finish (sample chip required)		

F39 & F40 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	600300	600400	600410
Power (LED)	28W	28W	36W
Delivered lms	1898	2078	2745
LPW	70	75	76
Diameter (A)	18"	23"	23"
Depth (D)	4"	4"	4"
Weight	8.1lb	9.9lb	9.9lb

## APPROVALS



# ERELLA™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

