

ERELLA™ - CEILING SURFACE

| | |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities: |



ERELLA™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Diffusers

Opal polycarbonate.

Luminaire orientation

Ceiling or wall mounted.

Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.


Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



ERELLA™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

600300 18", 1898 lms **600400** 23", 2078 lms **600410** 23", 2745 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. DIFFUSER

OP Opal Acrylic

D. FINISH

| | | | |
|---|--|---------------------------|-------------------------|
| WH White | BM Bronze Metallic Textured | MS Silver Metallic | AB Antique Brass |
| PB Polished Brass | SB Satin Brass | PC Polished Chrome | SN Satin Nickel |
| F39 Other painted finish (RAL number required) | F40 Other Non-RAL painted finish (sample chip required) | | |

F39 & F40 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

| Code | 600300 | 600400 | 600410 |
|---------------|--------|--------|--------|
| Power (LED) | 28W | 28W | 36W |
| Delivered lms | 1898 | 2078 | 2745 |
| LPW | 70 | 75 | 76 |
| Diameter (A) | 18" | 23" | 23" |
| Depth (D) | 4" | 4" | 4" |
| Weight | 8.1lb | 9.9lb | 9.9lb |

APPROVALS



ERELLA™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

