Fixture Code:	Quantities:
Project Name:	Fixture Type:



GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Mechanical

Luminaires mount directly over a junction box (by others - North America only).

L70 @25°C (77°F)

> 50,000 hrs.

OPTICS & FEATURES





Suspended Direct/Indirect

Direct-indirect

Suspension

Single tube with three support cables.

Lens

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15′. Test switch fits a single gang box (not supplied).

HOW TO ORDER

A. LUMINAIRE

127010 23", 12714 lms 127020 29", 15439 lms 127030 33", 19334 lms 127040 46", 30973 lms

127050 56", 38150 lms

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

C. FINISH

WH White **BM** Bronze Metallic Textured MS Silver Metallic **AB** Antique Brass

PB Polished Brass SB Satin Brass **PC** Polished Chrome **SN** Satin Nickel

F39 Other painted finish (RAL number F40 Other Non-RAL painted finish

(sample chip required) required)

F39 & F40 have a one time set-up charge regardless of quantity.

D. LENS

OP Opal

E. DIMMING

DA DALI Drivers **DX** DMX Drivers

F. OPTIONS

RE Remote Emergency (max distance **CB** Cradle Bars SW Swivel Canopy (42 Degrees)

10ft., 120/277V)

G. SUSPENSION LENGTHS

S1 6" additional suspension length **S2** 12" additional suspension length **S3** 18" additional suspension length **S4** 24" additional suspension length

TECHNICAL DATA

LUMINAIRE

Code	127010	127020	127030	127040	127050
Power (LED)	128W	149W	170W	283W	350W
Delivered Ims	12714	15439	19334	30973	38150
LPW	100	104	114	109	109
Diameter (A)	23"	29"	33"	46"	56"
Depth (D)	7"	9"	9"	12"	18"
Height (H)	17.5"	23"	23"	23"	29.5"

APPROVALS











DIMENSIONAL DIAGRAMS

