

# ERELLA™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ERELLA™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

### Dust covers

Clear polycarbonate.

### Mechanical

Luminaires mount directly over a junction box (by others - North America only).

### L70 @25°C (77°F)

> 50,000 hrs.

### Suspension

Single tube with three support cables.

### Lens

Acrylic.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.


### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

## OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect

# ERELLA™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**127010** 23", 12714 lms

**127050** 56", 38150 lms

**127020** 29", 15439 lms

**127030** 33", 19334 lms

**127040** 46", 30973 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**PB** Polished Brass

**F39** Other painted finish (RAL number required)

**BM** Bronze Metallic Textured

**SB** Satin Brass

**F40** Other Non-RAL painted finish (sample chip required)

**MS** Silver Metallic

**PC** Polished Chrome

**AB** Antique Brass

**SN** Satin Nickel

---

F39 & F40 have a one time set-up charge regardless of quantity.

### D. LENS

**OP** Opal

### E. DIMMING

**DA** DALI Drivers

**DX** DMX Drivers

### F. OPTIONS

**RE** Remote Emergency (max distance 10ft., 120/277V)

**CB** Cradle Bars

**SW** Swivel Canopy (42 Degrees)

### G. SUSPENSION LENGTHS

**S1** 6" additional suspension length

**S2** 12" additional suspension length

**S3** 18" additional suspension length

**S4** 24" additional suspension length



# ERELLA™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>127010</b>	<b>127020</b>	<b>127030</b>	<b>127040</b>	<b>127050</b>
<b>Power (LED)</b>	128W	149W	170W	283W	350W
<b>Delivered lms</b>	12714	15439	19334	30973	38150
<b>LPW</b>	100	104	114	109	109
<b>Diameter (A)</b>	23"	29"	33"	46"	56"
<b>Depth (D)</b>	7"	9"	9"	12"	18"
<b>Height (H)</b>	17.5"	23"	23"	23"	29.5"

---

## APPROVALS



IP20

# ERELLA™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

