

ERELLA™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 5

ERELLA™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Suspension

Single tube with three support cables.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Lens

Acrylic.

Dust covers

Clear polycarbonate.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Mechanical

Luminaires mount directly over a junction box (by others - North America only).

Remote Emergency


Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).


L70 @25°C (77°F)

> 50,000 hrs.

OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect



ERELLA™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

127010 23", 12714 lms
127050 56", 38150 lms

127020 29", 15439 lms

127030 33", 19334 lms

127040 46", 30973 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

BM Bronze Metallic Textured

MS Silver Metallic

AB Antique Brass

PB Polished Brass

SB Satin Brass

PC Polished Chrome

SN Satin Nickel

F39 Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

D. LENS

OP Opal

E. DIMMING

DA DALI Drivers

DX DMX Drivers

F. OPTIONS

RE Remote Emergency (max distance 10ft., 120/277V)

CB Cradle Bars

SW Swivel Canopy (42 Degrees)

G. SUSPENSION LENGTHS

S1 6" additional suspension length

S2 12" additional suspension length

S3 18" additional suspension length

S4 24" additional suspension length



ERELLA™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	127010	127020	127030	127040	127050
Power (LED)	128W	149W	170W	283W	350W
Delivered lms	12714	15439	19334	30973	38150
LPW	100	104	114	109	109
Diameter (A)	23"	29"	33"	46"	56"
Depth (D)	7"	9"	9"	12"	18"
Height (H)	17.5"	23"	23"	23"	29.5"

APPROVALS



ERELLA™ - SUSPENDED

DIMENSIONAL DIAGRAMS

