

FIN™ - WALL RECESSED EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



FIN™ - WALL RECESSED EXTERIOR

GENERAL SPECIFICATION

Housing

Die-cast and extruded aluminum.

External Screws

Stainless steel.

Lens

Etched glass.

Gaskets

One piece silicone.

Finish

Silver powder coated RAL9006 or black powder coated.

Drivers

HPF electronic 120-277V (EU-240V).

Cable entry

M20 cable gland.

Recessed housing

Die formed stainless steel.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


OPTICS & FEATURES



Ext-Wall Recessed
Uplight



Ext-Wall Recessed
Downlight



Assymetrical

FIN™ - WALL RECESSED EXTERIOR

HOW TO ORDER

A. LUMINAIRE

8306501 16W LED, 1215 lms

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

AG Anthracite Gray

GR Light Gray (RAL 9006)

D. SPECIFY ROUGH-IN HOUSING (REQUIRED)

8306590 Rough-In Housing

E. OPTIONS

DB Dimming (0-10V, 10%, 120V only)

FIN™ - WALL RECESSED EXTERIOR

TECHNICAL DATA

LUMINAIRE

Code	8306501
Distribution	16W LED
Delivered lms	1215
LPW	76

APPROVALS



IP66

FIN™ - WALL RECESSED EXTERIOR

DIMENSIONAL DIAGRAMS

