

# FIN™ - WALL RECESSED EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# FIN™ - WALL RECESSED EXTERIOR

## GENERAL SPECIFICATION

### Housing

Die-cast and extruded aluminum.

### External Screws

Stainless steel.

### Lens

Etched glass.

### Gaskets

One piece silicone.

### Finish

Silver powder coated RAL9006 or black powder coated.

### Drivers

HPF electronic 120-277V (EU-240V).

### Cable entry

M20 cable gland.

### Recessed housing

Die formed stainless steel.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Ext-Wall Recessed  
Uplight



Ext-Wall Recessed  
Downlight



Assymetrical

# FIN™ - WALL RECESSED EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**8306501** 16W LED, 1215 lms

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**AG** Anthracite Gray

**GR** Light Gray (RAL 9006)

### D. SPECIFY ROUGH-IN HOUSING (REQUIRED)

**8306590** Rough-In Housing

### E. OPTIONS

**DB** Dimming (0-10V, 10%, 120V only)

# FIN™ - WALL RECESSED EXTERIOR

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>8306501</b>
<b>Distribution</b>	16W LED
<b>Delivered lms</b>	1215
<b>LPW</b>	76

---

## APPROVALS



IP66

# FIN™ - WALL RECESSED EXTERIOR

## DIMENSIONAL DIAGRAMS

