Project Name:	Fixture Type:
Fixture Code:	Quantities:



### **GENERAL SPECIFICATION**

Housing

Die-cast and extruded aluminum.

Lens

Etched glass.

Finish

Silver powder coated RAL9006 or black powder coated.

Cable entry

M20 cable gland.

**Delivered Lumens** 

Delivered lumens & LPW based on 3000K (min 80 CRI).

**OPTICS & FEATURES** 



Ext-Wall Recessed Uplight



Ext-Wall Recessed Downlight



**External Screws** 

One piece silicone.

Recessed housing

Die formed stainless steel.

HPF electronic 120-277V (EU-240V).

Stainless steel.

Gaskets

Drivers

Assymetrical

### **HOW TO ORDER**

#### **A. LUMINAIRE**

**8306501** 16W LED, 1215 lms

B. CCT

**30** 3000K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

BL Black AG Anthracite Gray GR Light Gray (RAL 9006)

### D. SPEICFY ROUGH-IN HOUSING (REQUIRED)

8306590 Rough-In Housing

### **E. OPTIONS**

**DB** Dimming (0-10V, 10%, 120V only)

### **TECHNICAL DATA**

#### **LUMINAIRE**

Code 8306501 Distibution 16W LED **Delivered Ims** 1215 LPW 76

### **APPROVALS**











### **DIMENSIONAL DIAGRAMS**

