

FLUID™ SHORT SPECIFICATION SHEET



Fixture Type	Fixture Code	Quantities

1 HOW TO ORDER

1. LUMINAIRE

FLDW Wall

Mounts to 2"x4" swtich box (supplied by others).

2. DIAMETER

DR04 4" 1 DR06 6"

3. DIRECTION

DT1 Direct (10" housing) ^{1 2} **DT2** Direct/Indirect (12"/14" housing) ³

¹ Fluid 4" will be available in January 2026.

¹ Wall mount "direct only" can be installed pointing up or down.

² Direct will have a 10" tall housing.

 $^{^3}$ Direct/Indirect 4" diameter will have a 12" tall housing & 6" diameter will have a 14" tall housing.



4. LIGHT SOURCE

DN01 LEDs / Multi-Array Optics ¹ **DN02** COB / Reflector

- * All data based on max output and nominal values.
- ¹ Available for 6" diameter only.

5. CRI

CR00 Not required (For Amber **CR80** CRI 80+ Light)

6. CCT

CTA62 Amber (Turtle Friendly) 1

7. DISTRIBUTION DIRECT

BAT3 Type II ¹ **BA03** 3° ² **BA15** 15° ³ 4 ⁵

BA30 30° 34 5 BA50 50° 34 BA70 70° 35

8. DISTRIBUTION INDIRECT

BB00 Not required BB03 3° 1 BB15 15° 23 4 BB30 30° 23 4

BB50 50° 23 BB70 70° 24

¹ Available for 6" diameter with LEDs / Multi-Array Optics and 50° direct distribution.

¹ Available for 6" Direct, with LEDs / Multi-Array Optics distribution, not recommended for Indirect use. Available with Direct lumens of 2000, 2500 and 3000.

² Available for 6" with LEDs / Multi-Array Optics distribution and Wall mount. There may be a +/- 250K variance in color temperature. The head is not adjustable.

³ Available for 6" with LEDs / Multi-Array Optics distribution.

⁴ Available for 6" with COB / Reflector.

⁵ Available for 4" with COB / Reflector.

¹ Available for 6" with LEDs, Indirect, and Wall version only. There may be a +/- 250K variance in color temperature. The head is not adjustable.

² Available for 6" with LEDs / Multi-Array Optics distribution.

³ Available for 6" with COB / Reflector.

⁴ Available for 4" with COB / Reflector.



9. LUMENS DIRECT

LMA0200 2000 lms LMA0300 3000 lms LMA0005 59 lms ¹ LMA0040 400 lms ²

LMA0400 4000 lms 4

10. LUMENS INDIRECT

LMB0000 Not required LMB0200 2000 lms LMB0300 3000 lms LMB0005 59 lms 1

11. VOLTAGE

V1 120/277V V2 240V 1

12. DIMMING

DA11 0-10V Dimming 1.0% - Arctic **DA12** 0-10V Dimming 1.0% -**DA01** 0-10V Dimming 1.0% DA21 DALI Dimming 1.0% 3

> driver1 3 Desert driver ^{2 3}

13. FIXTURE FINISH

FA01 White FA02 Black Metallic - Textured FA20 Silver Metallic - Textured FA27 Wood grain - Light Cherry 1

FA47 Bronze Metallic - Textured FA46 Charcoal Metallic -FA28 Wood grain - Dark Walnut ¹FA30 Wood grain - White Oak ¹

Textured

¹ Available for 6" diameter with 3° Direct distribution only.

² Available for 6" diameter and Amber (Turtle Friendly) light only.

³ Available for 4" and 6" diameters with Direct only.

[&]quot; Available for 6" diameter and Direct only.

¹ Available for 3° Indirect distribution.

¹ Not available in North America.

¹ Capable of operating at -30 °C (-22 °F) to ambient temperature.

² Capable of operating at +50 °C (+122 °F) ambient temperature.

³ Consult factory.

¹ Longer than normal lead times may apply, consult factory.



14. BEZEL FINISH

FB01 White FB02 Black Metallic - Textured FB20 Silver Metallic - Textured FB46 Charcoal Metallic - Textured Textured

FB47 Bronze Metallic - Textured

Shatterproof lens available, consult factory.