





FLUID™


SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 HOW TO ORDER

LUMINAIRE	DIAMETER	DIRECTION	LIGHT SOURCE
<p>FLDW Wall</p> <p>Mounts to 2"x4" switch box (supplied by others).</p>	<p>DR04 4" ¹</p> <p>DR06 6"</p> <p>¹ Fluid 4" will be available in January 2026. ² Tilttable head available on 6" diameter only.</p>	<p>DT1 Direct (10" housing) ^{1 2}</p> <p>DT2 Direct/Indirect (12"/14" housing) ³</p> <p>¹ Wall mount "direct only" can be installed pointing up or down. ² Direct will have a 10" tall housing. ³ Direct/Indirect 4" diameter will have a 12" tall housing & 6" diameter will have a 14" tall housing.</p>	<p>DN01 LEDs / Multi-Array Optics ¹</p> <p>DN02 COB / Reflector</p> <p>* All data based on max output and nominal values. ¹ Available for 6" diameter only.</p>
CRI	CCT	DISTRIBUTION DIRECT	
<p>CR00 Not required (For Amber Light)</p> <p>CR80 CRI 80+</p>	<p>CTA27 2700K</p> <p>CTA30 3000K</p> <p>CTA35 3500K</p> <p>CTA40 4000K</p> <p>CTA62 Amber (Turtle Friendly) ¹</p> <p>¹ Available for 6" diameter with LEDs / Multi-Array Optics and 50° direct distribution.</p>	<p>BAT2 Type II ¹</p> <p>BAT3 Type III ¹</p> <p>BAT4 Type IV ¹</p> <p>BA03 3° ²</p> <p>BA15 15° ^{3 4 5}</p> <p>BA30 30° ^{3 4 5}</p> <p>BA50 50° ^{3 4}</p> <p>BA70 70° ^{3 5}</p> <p>¹ Available for 6" Direct (2000, 2500 and 3000 lumens), with LEDs / Multi-Array Optics distribution, not recommended for Indirect use. ² Available for 6" with LEDs / Multi-Array Optics distribution and Wall mount. There may be a +/- 250K variance in color temperature. The head is not adjustable. ³ Available for 6" with LEDs / Multi-Array Optics distribution. ⁴ Available for 6" with COB / Reflector. ⁵ Available for 4" with COB / Reflector.</p>	

<p>DISTRIBUTION INDIRECT</p> <p>BB00 Not required</p> <p>BB03 3° ¹</p> <p>BB15 15° ^{2 3 4}</p> <p>BB30 30° ^{2 3 4}</p> <p>BB50 50° ^{2 3}</p> <p>BB70 70° ^{2 4}</p> <p>¹ Available for 6" with LEDs, Indirect, and Wall version only. There may be a +/- 250K variance in color temperature. The head is not adjustable. ² Available for 6" with LEDs / Multi-Array Optics distribution. ³ Available for 6" with COB / Reflector. ⁴ Available for 4" with COB / Reflector.</p>	<p>LUMENS DIRECT</p> <p>LMA0005 59 lms ¹</p> <p>LMA0040 400 lms ²</p> <p>LMA0200 2000 lms</p> <p>LMA0250 2500 lms</p> <p>LMA0300 3000 lms</p> <p>LMA0350 3500 lms ³</p> <p>LMA0400 4000 lms ⁴</p> <p>¹ Available for 6" diameter with 3° Direct distribution only. ² Available for 6" diameter and Amber (Turtle Friendly) light only. ³ Available for 4" and 6" diameters with Direct only. ⁴ Available for 6" diameter and Direct only.</p>	<p>LUMENS INDIRECT</p> <p>LMB0000 Not required</p> <p>LMB0005 59 lms ¹</p> <p>LMB0200 2000 lms</p> <p>LMB0250 2500 lms</p> <p>LMB0300 3000 lms</p> <p>¹ Available for 3° Indirect distribution.</p>	<p>VOLTAGE</p> <p>V1 120/277V</p> <p>V2 240V ¹</p> <p>¹ Not available in North America.</p>
<p>DIMMING</p> <p>DA01 0-10V Dimming 1.0%</p> <p>DA11 0-10V Dimming 1.0% - Arctic driver^{1 3}</p> <p>DA12 0-10V Dimming 1.0% - Desert driver^{2 3}</p> <p>DA21 DALI Dimming 1.0% ³</p> <p>¹ Capable of operating at -30°C (-22°F) to ambient temperature. ² Capable of operating at +50°C (+122°F) ambient temperature. ³ Consult factory.</p>	<p>FIXTURE FINISH</p> <p>FA01 White - Textured</p> <p>FA02 Black Metallic - Textured</p> <p>FA20 Silver Metallic - Textured</p> <p>FA27 Wood grain - Light Cherry ¹</p> <p>FA28 Wood grain - Dark Walnut ¹</p> <p>FA30 Wood grain - White Oak ¹</p> <p>FA46 Charcoal Metallic - Textured</p> <p>FA47 Bronze Metallic - Textured</p> <p>¹ Longer than normal lead times may apply, consult factory.</p>	<p>BEZEL FINISH</p> <p>FB01 White - Textured</p> <p>FB02 Black Metallic - Textured</p> <p>FB20 Silver Metallic - Textured</p> <p>FB46 Charcoal Metallic - Textured</p> <p>FB47 Bronze Metallic - Textured</p> <p>Shatterproof lens available, consult factory.</p>	