



FLUID™

SHORT SPECIFICATION SHEET



Fixture Type

Fixture Code

Quantities

1 HOW TO ORDER

1. LUMINAIRE

FLDW Wall

Mounts to 2"x4" switch box (supplied by others).

2. DIAMETER

DR06 6"

3. DIRECTION

DT1 Direct 10" housing ¹

DT2 Direct/Indirect 14" housing

¹ Wall mount direct only can be installed pointing up or down.

Direct will have a 10" housing

Direct/Indirect will have a 14" housing

4. LIGHT SOURCE

DN01 LEDs / Multi-Array Optics **DN02** COB / Reflector

All data based on max output and nominal values.

5. CRI

CR00 Not required (For Amber Light) **CR80** CRI 80+

6. CCT

CTA27 2700K **CTA30** 3000K **CTA35** 3500K **CTA40** 4000K
CTA62 Amber (Turtle Friendly) ¹

¹ Available for LED Direct only with 50° direct distribution.

7. DISTRIBUTION DIRECT

BAT2 Type II ¹ **BAT3** Type III ¹ **BA03** 3° ² **BA15** 15° ⁴
BA30 30° ⁴ **BA50** 50° ⁴ **BA70** 70° ³

¹ Available for Direct and LEDs / Multi-Array Optics distribution only, not recommended for Indirect use. Available with Direct lumens of 2000 and 3000, not 4000.

² Available for LEDs / Multi-Array Optics distribution. There may be a +/- 250K variance in color temperature. The head is not adjustable.

³ Available for LEDs / Multi-Array Optics distribution.

⁴ Available for LEDs / Multi-Array Optics distribution or COB / Reflector.

8. DISTRIBUTION INDIRECT

BB00 Not required **BB03** 3° ¹ **BB15** 15° ² **BB30** 30° ²
BB50 50° ³ **BB70** 70° ²

¹ Available for LEDs and Indirect only. There may be a +/- 250K variance in color temperature. The head is not adjustable.

² Available for LEDs / Multi-Array Optics distribution only.

³ Available for LEDs / Multi-Array Optics distribution and COB / Reflector.

9. LUMENS DIRECT

LMA0005 59 lms ¹ **LMA0040** 400 lms ² **LMA0200** 2000 lms **LMA0300** 3000 lms
LMA0400 4000 lms ³

¹ Available for 3° Direct distribution.

² Available for Amber (Turtle Friendly) light.

³ Available for Direct only, 15°, 30°, 50°, and 70°.

10. LUMENS INDIRECT

LMB0000 Not required **LMB0005** 59 lms ¹ **LMB0200** 2000 lms **LMB0300** 3000 lms

¹ Available for 3° Indirect distribution.

11. VOLTAGE

V1 120/277V **V2** 240V ¹

¹ Not available in North America

12. DIMMING

DA01 0-10V Dimming 1.0% **DA11** 0-10V Dimming 1.0% - Arctic driver^{1 3} **DA12** 0-10V Dimming 1.0% - Desert driver ^{2 3} **DA21** DALI Dimming 1.0% ³

¹ Capable of operating at -30 °C (-22 °F) to ambient temperature

² Capable of operating at +50 °C (+122 °F) ambient temperature

³ Consult factory

13. FIXTURE FINISH

FA01 White **FA02** Black Metallic - Textured **FA20** Silver Metallic - Textured **FA27** Wood grain - Light Cherry ¹
FA28 Wood grain - Dark Walnut ¹**FA46** Charcoal Metallic - Textured **FA47** Bronze Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

14. BEZEL FINISH

FB01 White **FB02** Black Metallic - Textured **FB20** Silver Metallic - Textured **FB46** Charcoal Metallic - Textured
FB47 Bronze Metallic - Textured

Shatterproof lens available, consult factory.