FLUID™

SHORT SPECIFICATION SHEET



FIXTURE TYPE	FIXTURE CODE	QUANTITIES

1 HOW TO ORDER

LUMINAIRE

FLDW Wall

Mounts to 2"x4" swtich box (supplied by others).

DIAMETER

DR04 4" [1]

DR06 6"

[1] Fluid 4" will be available in January 2026. [2] Tiltable head available on 6" diameter only.

DIRECTION

DT1 Direct (10" housing) [1] [2]

DT2 Direct/Indirect (12"/14" housing) [3]

[1] Wall mount "direct only" can be installed pointing up or down. [2] Direct will have a 10" tall housing.
[3] Direct/Indirect 4" diameter will have a 12" tall housing & 6" diameter will have a 14" tall housing.

LIGHT SOURCE

DN01 LEDs / Multi-Array Optics [1]

DN02 COB / Reflector

* All data based on max output and nominal values.
[1] Available for 6" diameter only.

CRI

CR00 Not required (For Amber Light)

CR80 CRI 80+

CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

CTA62 Amber (Turtle Friendly) [1]

[1] Available for 6" diameter with LEDs / Multi-Array Optics and 50° direct distribution.

DISTRIBUTION DIRECT

BAT2 Type II [1]

BAT3 Type III [1]

BAT4 Type IV [1]

BA03 3° [2]

BA15 15° [3] [4] [5]

BA30 30° [3] [4] [5]

BA50 50° [3] [4]

BA70 70° [3] [5]

[1] Available for 6" Direct (2000, 2500 and 3000 lumens), with LEDs / Multi-Array Optics distribution, not recommended for Indirect use.
[2] Available for 6" with LEDs / Multi-Array Optics distribution and Wall mount. There may be a +/- 250K variance in color temperature. The head is not adjustable. [3] Available for 6" with LEDs / Multi-Array Optics distribution. [4] Available for 6" with COB / Reflector.
[5] Available for 4" with COB / Reflector.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

DISTRIBUTION INDIRECT

BB00 Not required

BB03 3° [1]

BB15 15° [2 3 4]

BB30 30° [2 3 4]

BB50 50° [2 3]

BB70 70° [2 4]

[1] Available for 6" with LEDs, Indirect, and Wall version only. There may be a +/- 250K variance in color temperature. The head is not adjustable. [2] Available for 6" with LEDs / Multi-Array Optics distribution. [3] Available for 6" with COB / Reflector.
[4] Available for 4" with COB / Reflector.

LUMENS DIRECT

LMA0005 59 lms [1]

LMA0040 400 lms [2]

LMA0200 2000 lms

LMA0250 2500 lms

LMA0300 3000 lms

LMA0350 3500 lms [3]

LMA0400 4000 lms [4]

[1] Available for 6" diameter with 3° Direct distribution only. [2] Available for 6" diameter and Amber (Turtle Friendly) light only.
[3] Available for 4" and 6" diameters with Direct only. [4] Available for 6" diameter and Direct only.

LUMENS INDIRECT

LMB0000 Not required

LMB0005 59 lms [1]

LMB0200 2000 lms

LMB0250 2500 lms

LMB0300 3000 lms

[1] Available for 3° Indirect distribution.

VOLTAGE

V1 120/277V

V2 240V [1]

[1] Not available in North America.

DIMMING

DA01 0-10V Dimming 1.0%

DA11 0-10V Dimming 1.0% - Arctic driver [1 3]

DA12 0-10V Dimming 1.0% - Desert driver [2 3]

DA21 DALI Dimming 1.0% [3]

[1] Capable of operating at -30°C (-22°F) to ambient temperature. [2] Capable of operating at +50°C (+122°F) ambient temperature.
[3] Consult factory.

FIXTURE FINISH

FA01 White - Textured

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA27 Wood grain - Light Cherry [1]

FA28 Wood grain - Dark Walnut [1]

FA30 Wood grain - White Oak [1]

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

[1] Longer than normal lead times may apply, consult factory.

BEZEL FINISH

FB01 White - Textured

FB02 Black Metallic - Textured

FB20 Silver Metallic - Textured

FB46 Charcoal Metallic - Textured

FB47 Bronze Metallic - Textured

Shatterproof lens available, consult factory.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice