




FLUID™

SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 HOW TO ORDER

1. LUMINAIRE

FLDW Wall

Mounts to 2"x4" switch box (supplied by others).

2. DIAMETER

DR04 4" ¹

DR06 6"

¹ Fluid 4" will be available in January 2026. ² Tilttable head available on 6" diameter only.

3. DIRECTION

DT1 Direct (10" housing) ^{1 2}

DT2 Direct/Indirect (12"/14"
housing) ³

¹ Wall mount "direct only" can be installed pointing up or down. ² Direct will have a 10" tall housing.

³ Direct/Indirect 4" diameter will have a 12" tall housing & 6" diameter will have a 14" tall housing.

4. LIGHT SOURCE

DN01 LEDs / Multi-Array Optics ¹ **DN02** COB / Reflector

* All data based on max output and nominal values.

¹ Available for 6" diameter only.

5. CRI

CR00 Not required (For Amber Light) **CR80** CRI 80+

6. CCT

CTA27 2700K **CTA30** 3000K **CTA35** 3500K **CTA40** 4000K
CTA62 Amber (Turtle Friendly) ¹

¹ Available for 6" diameter with LEDs / Multi-Array Optics and 50° direct distribution.

7. DISTRIBUTION DIRECT

BAT2 Type II ¹ **BAT3** Type III ¹ **BAT4** Type IV ¹ **BA03** 3° ²
BA15 15° ^{3 4 5} **BA30** 30° ^{3 4 5} **BA50** 50° ^{3 4} **BA70** 70° ^{3 5}

¹ Available for 6" Direct (2000, 2500 and 3000 lumens), with LEDs / Multi-Array Optics distribution, not recommended for Indirect use.

² Available for 6" with LEDs / Multi-Array Optics distribution and Wall mount. There may be a +/- 250K variance in color temperature. The head is not adjustable. ³ Available for 6" with LEDs / Multi-Array Optics distribution. ⁴ Available for 6" with COB / Reflector.

⁵ Available for 4" with COB / Reflector.

8. DISTRIBUTION INDIRECT

BB00 Not required **BB03** 3° ¹ **BB15** 15° ^{2 3 4} **BB30** 30° ^{2 3 4}
BB50 50° ^{2 3} **BB70** 70° ^{2 4}

¹ Available for 6" with LEDs, Indirect, and Wall version only. There may be a +/- 250K variance in color temperature. The head is not adjustable. ² Available for 6" with LEDs / Multi-Array Optics distribution. ³ Available for 6" with COB / Reflector.

⁴ Available for 4" with COB / Reflector.

9. LUMENS DIRECT

LMA0005 59 lms ¹ **LMA0040** 400 lms ² **LMA0200** 2000 lms **LMA0300** 3000 lms
LMA0400 4000 lms ⁴

¹ Available for 6" diameter with 3° Direct distribution only. ² Available for 6" diameter and Amber (Turtle Friendly) light only.

³ Available for 4" and 6" diameters with Direct only. ⁴ Available for 6" diameter and Direct only.

10. LUMENS INDIRECT

LMB0000 Not required **LMB0005** 59 lms ¹ **LMB0200** 2000 lms **LMB0300** 3000 lms

¹ Available for 3° Indirect distribution.

11. VOLTAGE

V1 120/277V **V2** 240V ¹

¹ Not available in North America.

12. DIMMING

DA01 0-10V Dimming 1.0% **DA11** 0-10V Dimming 1.0% - Arctic driver^{1 3} **DA12** 0-10V Dimming 1.0% - Desert driver^{2 3} **DA21** DALI Dimming 1.0% ³

¹ Capable of operating at -30 °C (-22 °F) to ambient temperature. ² Capable of operating at +50 °C (+122 °F) ambient temperature.

³ Consult factory.

13. FIXTURE FINISH

FA01 White **FA02** Black Metallic - Textured **FA20** Silver Metallic - Textured **FA27** Wood grain - Light Cherry ¹
FA28 Wood grain - Dark Walnut ¹ **FA30** Wood grain - White Oak ¹ **FA46** Charcoal Metallic - Textured **FA47** Bronze Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

14. BEZEL FINISH

FB01 White

FB02 Black Metallic - Textured

FB20 Silver Metallic - Textured

FB46 Charcoal Metallic -
Textured

FB47 Bronze Metallic - Textured

Shatterproof lens available, consult factory.