




FLUTE™

SHORT SPECIFICATION SHEET



Fixture Type


Fixture Code

Quantities

1 DESCRIPTION

FLUTE's shape shifts the traditional block form factor into a cutting-edge cyber style. The fluting along the flank emits a side glow that radiates an electrifying detail and provides a lightweight appearance to an already compact form factor. The hourglass contour jacks up profile design with an aerodynamic quality. **FLUTE** is the optimal complement for tech-age modern design and interiors with intricate detailing.

2 MOUNTING & OPTICS



3 APPROVALS



4 GENERAL SPECIFICATION

BODY

Aluminum.

FINISH

Powder coated.

POWER CABLE

Silver braided.

SUSPENSION

Steel cables.

MECHANICAL

Align N' Lock™ joiner ensures zero light leak and a simple installation.

Luminaires mount directly over J box (by others).

POE

Can be integrated into your data network via Power over Ethernet connectivity.

REMOTE EMERGENCY

Emergency option provides a 1.5 hour (3hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch. Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

DRIVERS

HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

REPORTED L70 @25°C (77°F)

>108000 hrs @3000 lms/ft (9800 lm/m)

DELIVERED LUMENS

Delivered lumens & LPW based on 4000K CRI 80+

DESIGNED BY

Serge Cornelissen.

DIFFUSER

Opal acrylic. Supplied with a seamless roll (up to 24ft), to be trimmed and installed in the field.

BIOS

For circadian lighting, consult factory.

SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.

TUNABLE WHITE

Tunable White range from 2700K to 6500K is available; contact the factory for details.

ESTIMATED L70 @25°C (77°F)

>196000 hrs @3000 lms/ft (9800 lm/m)

APPROVALS













Damp Rated.

DESIGN

US Pat. No. D967,491 US Pat. No. D969,389











5 DESIGN OPTIONS

FIXTURE FINISH

							
White	Black Metallic - Textured	Silver Metallic - Textured	Gold Metallic - Textured	Wood grain - Light Cherry ¹	Wood grain - Dark Walnut ¹	Midnight Blue Metallic - Textured	Copper Metallic
							
Charcoal Metallic - Textured	Bronze Metallic - Textured	Champagne Metallic	Red Metallic - Textured				

¹ Longer than normal lead times may apply, consult factory.

CANOPY FINISH

							
White	Black Metallic - Textured	Silver Metallic - Textured	Gold Metallic - Textured	Midnight Blue Metallic - Textured	Copper Metallic	Charcoal Metallic - Textured	Bronze Metallic - Textured
							
Champagne Metallic	Red Metallic - Textured						

6 HOW TO ORDER

A. LUMINAIRE

FLUP1P Direct **FLUP2P** Direct/Indirect

Data shown based on max values, consult Performance Data download for more details. Non Illuminated Reveal versions available, consult factory for details.

One power cord for every 50 linear feet.

B. LENGTH OF RUN

SFA _ _ _ _

Minimum length to order is 4ft and orders to be in 2ft increments. For 6 inch increments, consult factory.

Example: 4ft = SFA0400

Example: 10ft = SFA1000

Example: 50ft = SFA5000

For runs over 50ft in length, consult factory.

C. MAX LENGTH PER SECTION

SL04 4ft **SL06** 6ft **SL08** 8ft **SL10** 10ft
SL12 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4 10ft segments. For special requirements, please contact sales@betacalco.com.

D. LM/FT (DIRECT)

LPF020 200 lm/ft **LPF040** 400 lm/ft **LPF060** 600 lm/ft **LPF080** 800 lm/ft
LPF100 1000 lm/ft **LPF120** 1200 lm/ft **LPF140** 1400 lm/ft

E. LM/FT (INDIRECT)

LPG000 Not required **LPG020** 200 lm/ft **LPG040** 400 lm/ft **LPG060** 600 lm/ft
LPG080 800 lm/ft **LPG100** 1000 lm/ft **LPG120** 1200 lm/ft **LPG140** 1400 lm/ft
LPG165 1650 lm/ft

F. CRI

CR80 CRI 80+ **CR90** CRI 90+

G. CCT - DIRECT

CTA27 2700K CTA30 3000K CTA35 3500K CTA40 4000K

H. CCT - INDIRECT

CTB00 Not required CTB27 2700K CTB30 3000K CTB35 3500K
CTB40 4000K

I. DIRECT DIFFUSER

DD2 Batwing DD4 Comfort

J. INDIRECT DIFFUSER

UD0 Not required UD1 Batwing UD3 Asymmetric ¹

¹ Available up to 1200 lms/ft.

K. UPLIGHT BLACKOUT PLATE

UB00 Not required UB_ _ Blackout plate ¹

¹ Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

L. VOLTAGE

V1 120/277V V2 240V ¹ V3 347V ² V4 Low Voltage ³

¹ V2 not available in North America.

² V3 available with DA01 dimming only.

³ V4 available with DA45 dimming only.

M. DIMMING

DA01 0-10V Dimming 1.0%	DA02 0-10V Dimming 0.1% ¹	DA20 DALI Dimming 0.1% ¹	DA21 DALI Dimming 1.0% ¹
DA30 DSI/switchDim ²	DA45 PoE ³		

¹ Not available with V3.

² Not available in North America.

³ Only available with V4.

N. CEILING TYPE

G1 Grid ceiling ¹	H1 Hard ceiling ²
-------------------------------------	-------------------------------------

¹ Combo kit includes installation to T-bar and through tile mount.

² Designed for drywall ceilings.

O. SUSPENSION

HLA03 3ft cable suspension	HLA06 6ft cable suspension	HLA09 9ft cable suspension
-----------------------------------	-----------------------------------	-----------------------------------

Special order available on lengths over 10ft and may be subject to longer lead times, consult factory.

P. FIXTURE FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry ¹	FA28 Wood grain - Dark Walnut ¹	FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic
FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic	FA53 Red Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

Q. CANOPY FINISH

CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured	CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured	CF47 Bronze Metallic - Textured
CF52 Champagne Metallic	CF53 Red Metallic - Textured		

R. EMERGENCY

E0 Not required **E1** Emergency system – Integral ¹ **E3** Emergency generated circuit ¹

¹ A drawing will be required at the time of ordering to determine the required number and location of the emergency sections or generator circuits. Not available in 347V.

S. CIRCUITS

CS1 Single circuit **CS2** Dual circuit ¹ **CS4** Emergency generated circuit ¹

¹ Only required if ordering Emergency system.

T. SENSORS

7 TECHNICAL DATA

LUMINAIRE


Data shown based on max values, consult Performance Data download for more details. Non Illuminated Reveal versions available, consult factory for details.

One power cord for every 50 linear feet.


Code	FLUP1P	FLUP2P
Light Direction	Direct	Direct/Indirect
Lms/Ft Direct	1400	1400
Lms/ft Indirect		1650
Watts/Ft Direct	13	13
Watts/Ft Indirect		13
LPW Direct	133	133
LPW Indirect		168

8 PERFORMANCE DATA


**DIRECT COMFORT DIFFUSER
(WITH SIDE REVEAL) (DD4)**

	LUMEN/FT	WATT/FT	LPW
	1400	13	107
	1200	11	110
	1000	9	113
	800	7	116
	600	5	121
	400	3	126
	200	2	133

INDIRECT BATWING (UD1)


	LUMEN/FT	WATT/FT	LPW
	1650	13	134
	1400	11	138
	1000	9	142
	800	7	146
	600	6	150
	400	4	155
	200	3	161
		1	168

**INDIRECT ASYMMETRIC
(UD3)**

	LUMEN/FT	WATT/FT	LPW
	1200	13	97
	1000	10	100
	800	9	102
	600	6	107
	400	4	109
	200	2	112


9 TM-30 DATA

CCT 2700K




CRI (Ra)	93
CRI (R9)	61
TM30 Rf	91
TM30 Rg	98
Duv	-0.0022

CCT 3000K




CRI (Ra)	92
CRI (R9)	58
TM30 Rf	92
TM30 Rg	100
Duv	-0.0003

CCT 3500K



CRI (Ra)	91
CRI (R9)	53
TM30 Rf	90
TM30 Rg	99
Duv	-0.0007

CCT 4000K



CRI (Ra)	93
CRI (R9)	64
TM30 Rf	90
TM30 Rg	98
Duv	0.0000

10 DIMENSIONAL DIAGRAMS

