

FLUTE™ - CONTINUOUS WALL

Project Name:


Fixture Type:

Fixture Code:

Quantities:



FLUTE™ - CONTINUOUS WALL



FLUTE™ - CONTINUOUS WALL

FLUTE's shape shifts the traditional block form factor into a cutting-edge cyber style. The fluting along the flank emits a side glow that radiates an electrifying detail and provides a lightweight appearance to an already compact form factor. The hourglass contour jacks up profile design with an aerodynamic quality. **FLUTE** is the optimal complement for tech-age modern design and interiors with intricate detailing.

GENERAL SPECIFICATION

Body

Aluminum.

PoE

Can be integrated into your data network via Power over Ethernet connectivity.

Remote emergency

Emergency option provides a 1.5 hour (3hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch. Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

Mechanical

Align N' Lock™ joiner ensures zero light leak and a simple installation. Luminaires mount directly over J box (by others).

Drivers

HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

Reported L70 @25°C (77°F)

>108000 hrs @3000 lms/ft (9800 lm/m)

Delivered lumens

Delivered lumens & LPW based on 4000K CRI 80+

Designed by

Serge Cornelissen.

Finish

Powder coated.

BIOS

For circadian lighting, consult factory.

Sensors

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.

Diffuser

Opal acrylic. Supplied with a seamless roll (up to 24ft), to be trimmed and installed in the field.

Tunable White

Tunable white available, consult factory.

Estimated L70 @25°C (77°F)

>196000 hrs @3000 lms/ft (9800 lm/m)

Approvals

Damp Rated.


Design

US Pat. No. D967,491 US Pat. No. D969,389


MOUNTING & OPTICS




Wall - up/down



Direct DD4



Indirect UD3



Declare



PoE



FLUTE™ - CONTINUOUS WALL

HOW TO ORDER

A. LUMINAIRE

FLUW1W Direct

FLUW2W Direct/Indirect

Data shown based on max values, consult Performance Data download for more details. Non Illuminated Reveal versions available, consult factory for details. One power cord for every 50 linear feet.

B. LENGTH OF RUN

SFA _ _ _ _

Minimum length to order is 4ft and orders to be in 2ft increments.

Example: 4ft = SFA0400

Example: 10ft = SFA1000

Example: 50ft = SFA5000

For runs over 50ft in length, consult factory.

C. MAX LENGTH PER SECTION

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4 10ft segments. For special requirements, please contact sales@betacalco.com.

D. LM/FT (DIRECT)

LPF020 200 lm/ft

LPF040 400 lm/ft

LPF060 600 lm/ft

LPF080 800 lm/ft

LPF100 1000 lm/ft

LPF120 1200 lm/ft

LPF140 1400 lm/ft

E. LM/FT (INDIRECT)

LPG000 Not required

LPG020 200 lm/ft

LPG040 400 lm/ft

LPG060 600 lm/ft

LPG080 800 lm/ft

LPG100 1000 lm/ft

LPG120 1200 lm/ft

F. CRI

CR80 CRI 80+

CR90 CRI 90+

G. CCT - DIRECT

CTA30 3000K

CTA35 3500K

CTA40 4000K

H. CCT - INDIRECT

CTB00 Not required

CTB30 3000K

CTB35 3500K

CTB40 4000K

I. DIRECT DIFFUSER

DD4 Comfort diffuser

J. UPLIGHT DIFFUSER

UD0 Not required

UD2 Opal diffuser

UD3 Asymmetric diffuser ¹

¹ Available up to 1200 lms/ft. The asymmetric distribution will be directed away from the wall.

FLUTE™ - CONTINUOUS WALL

K. UPLIGHT BLACKOUT PLATE

UB00 Not required **UB_ _** Blackout plate ¹

¹ Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

L. VOLTAGE

V1 120/277V **V2** 240V ¹ **V3** 347V ² **V4** Low Voltage ³

¹ V2 not available in North America.

² V3 available with DA01 dimming only.

³ V4 available with DA45 dimming only.

M. DIMMING

DA01 0-10V Dimming 1.0% **DA02** 0-10V Dimming 0.1% ¹ **DA20** DALI Dimming 0.1% ¹ **DA21** DALI Dimming 1.0% ¹
DA30 DSI/switchDim ² **DA45** PoE ³

¹ Not available with V3.

² Not available in North America.

³ Only available with V4.

N. FIXTURE FINISH

FA01 White **FA02** Black Metallic - Textured **FA20** Silver Metallic - Textured **FA25** Gold Metallic - Textured
FA27 Wood grain - Light Cherry ¹ **FA28** Wood grain - Dark Walnut ¹ **FA44** Midnight Blue Metallic - Textured **FA45** Copper Metallic
FA46 Charcoal Metallic - Textured **FA47** Bronze Metallic - Textured **FA52** Champagne Metallic **FA53** Red Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

O. EMERGENCY

E0 Not required **E2** Emergency system - Remote **E3** Emergency generated circuit ¹

¹ A drawing will be required at time of ordering to determine the required number and location of the emergency sections or generator circuits. Not available in 347V.

P. CIRCUITS

CS1 Single circuit **CS2** Dual circuit ¹ **CS4** Emergency generated circuit ¹

¹ Only required if ordering Emergency system.

Q. SENSORS

FLUTE™ - CONTINUOUS WALL


TECHNICAL DATA

LUMINAIRE

Data shown based on max values, consult Performance Data download for more details. Non Illuminated Reveal versions available, consult factory for details. One power cord for every 50 linear feet.

Code	FLUW1W	FLUW2W
Light Direction	Direct	Direct/Indirect
Lms/Ft Direct	1400	1400
Lms/ft Indirect		1650
Watts/Ft Direct	13	13
Watts/Ft Indirect		13
LPW Direct	133	133
LPW Indirect		168

FIXTURE FINISH



¹ Longer than normal lead times may apply, consult factory.


APPROVALS




FLUTE™ - CONTINUOUS WALL

PERFORMANCE DATA


DIRECT COMFORT DIFFUSER (WITH SIDE REVEAL) (DD4)

	LUMEN/FT	WATT/FT	LPW
	1400	13	107
	1200	11	110
	1000	9	113
	800	7	116
	600	5	121
	400	3	126
	200	2	133

INDIRECT BATWING (UD1)

	LUMEN/FT	WATT/FT	LPW
	1650	13	134
	1400	11	138
	1000	9	142
	800	7	146
	600	6	150
	400	4	155
	200	3	161
		1	168





INDIRECT ASYMMETRIC (UD3)

	LUMEN/FT	WATT/FT	LPW
	1200	13	97
	1000	10	100
	800	9	102
	600	6	107
	400	4	109
	200	2	112

FLUTE™ - CONTINUOUS WALL

DIMENSIONAL DIAGRAMS

Isometric Views



Top View [Uplight]




Bottom View [Downlight]


FLUTE™ - CONTINUOUS WALL

Wall Mount Configurations


4FT




6FT



8FT



10FT



12FT

