

# GEO™ - INGROUND EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# GEO™ - INGROUND EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

### Gasket

Silicone.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

### Drivers

HPF, electronic.

### Rough-in housing

Thermoplastic.

### Lens

10mm/0.36" tempered glass. IK 10 Mechanical resistant 20 Joule.

### Finish

Powder coated.

### Cable entry

PG13.5 gland for DIA 6-12mm/0.24-0.47" cables.

### Walk over

Static pressure load 6000Kg/13000lbs.

### Mechanical

For in-ground or wall installation in poured concrete.

## OPTICS & FEATURES



Ext-Inground

# GEO™ - INGROUND EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**8107300** 8107300

**8107302** 8107302

**8107304** 8107304

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**AG** Anthracite Gray

**GR** Light Gray

### D. ROUGH-IN HOUSING (REQUIRED)

**RIH5732** Rough-In Housing

## TECHNICAL DATA

### LUMINAIRE

Code	<b>8107300</b>	<b>8107302</b>	<b>8107304</b>
Power (LED)	1W	2W	3W
Distribution	Single Aperture	Twin Aperture	Triple Aperture
Initial Lumens	10	2 x 10	3 x 10
Max Surface Temp	63F	63F	63F

## APPROVALS



# GEO™ - INGROUND EXTERIOR

## DIMENSIONAL DIAGRAMS

