

Project Name: Fixture Type:

Fixture Code: Quantities:











The fluid lines of the Endless system transform into a closed-loop six-sided pendant. With rounded edges and a hollow form, HEXAGON adds a serene visual element and a unique alternative to the perfectionist ring. As a strong geometrical shape, Hexagon remains minimalist while conveying stability and lightness. Available with an acoustic panel in 6 colors.

GENERAL SPECIFICATION

Body

Extruded and die-cast aluminum.

Suspension

Steel cables.

Drivers

HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

Acoustic Panels Fire Rating

ASTM E84-2018 Class A.

Acoustic Panels Thickness

12mm (0.5")

Diffuser

Opal polycarbonate.

Reported L70 @25°C (77°F)

>102,000 hrs @ 1600 lumens/ft (5200 lumens/m)

Approvals

Damp Rated.

Seismic Bracing

Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

OPTICS & FEATURES













Declare

Indirect

Finish

Powder coated.

Power cable

Silver braided

Acoustic Panels NRC Rating

Acoustic Panels Material

100% recycled polyester fiber (PET).

Mechanical

Luminaires mount directly over J box (by others).

Sensors

Consult factory regarding sensor compatibility.

Delivered lumens

Delivered lumens & LPW based on 4000K CRI 90+

Designed by

Serge Cornelissen

HOW TO ORDER

A. LUMINAIRE

HEXG1P02 2ft, DirectHEXG1P03 3ft, DirectHEXG1P04 4ft, DirectHEXG1P05 5ft, Direct

HEXG1P06 6ft, DirectHEXG1P07 7ft, DirectHEXG2P02 2ft, Direct/IndirectHEXG2P03 3ft, Direct/IndirectHEXG2P04 4ft, Direct/IndirectHEXG2P05 5ft, Direct/IndirectHEXG2P06 6ft, Direct/IndirectHEXG2P07 7ft, Direct/Indirect

B. LM/FT (DIRECT)

LPF030 300 lm/ft ¹ **LPF050** 500 lm/ft ² **LPF070** 700 lm/ft ³

Black Metallic Textured is only available with direct lumens of 300 lm/ft and 500 lm/ft. Consult the Data Performance download page for details.

C. LM/FT (INDIRECT)

LPG000 Not required **LPG030** 300 lm/ft ¹ **LPG050** 500 lm/ft ² **LPG070** 700 lm/ft ³

LPG090 900 lm/ft 4

D. CRI

CR90 CRI 90+

E. CCT

CTA30 3000K **CTA35** 3500K **CTA40** 4000K

F. UPLIGHT DIFFUSER

UDO Not required **UD2** Opal diffuser

G. VOLTAGE

V1 120/277V

H. DIMMING

DA01 0-10V Dimming 1.0%

I. FIXTURE FINISH

FA01 White FA02 Black Metallic Textured ¹ FA20 Silver Metallic Textured

J. CANOPY FINISH

CF01 White **CF02** Black Metallic Textured **CF20** Silver Metallic Textured

K. ACOUSTIC PANEL COLOR

AP00 Not requiredAP02 CitrusAP04 WhiteAP08 Red CoffeeAP11 Light GrayAP13 Apple GreenAP22 BlueAP26 Sesame GrayAP27 BlackAP47 Navy PeonyAP60 Pure RedAP73 Cloudburst

AP89 Douglas Fir APW01 Oak

Acoustic panels exceeding 48" will have one seam. All other dimensions will be seamless.

For accompanying non-illuminating acoustic panels, see our Acoustic Circles, Quads, Triangles, and Ellipse spec pages.

Contact factory for larger sizes and additional colors.



¹ Not available with HEXG2P02 (2ft Direct/Indirect).

¹ Black Metallic Textured is only available with direct lumens of 300 lm/ft and 500 lm/ft.

L. CIRCUITS

CS1 Single circuit

CS2 Dual circuit

TECHNICAL DATA

LUMINAIRE

Code	HEXG1P02	HEXG1P03	HEXG1P04	HEXG1P05	HEXG1P06	HEXG1P07
Size	2ft	3ft	4ft	5ft	6ft	7ft
Light Direction	Direct	Direct	Direct	Direct	Direct	Direct
Wattage	69	106	138	175	207	244
Direct Ims	4300	6500	8500	10800	12700	15000
Indirect Ims						
LPW	61	61	61	61	61	61
Code	HEXG2P02	HEXG2P03	HEXG2P04	HEXG2P05	HEXG2P06	HEXG2P07
Size	2ft	3ft	4ft	5ft	6ft	7ft
Size Light Direction	2ft Direct/Indirect	3ft Direct/Indirect	4ft Direct/Indirect	5ft Direct/Indirect	6ft Direct/Indirect	7ft Direct/Indirect
Light Direction	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect
Light Direction Wattage	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect 299	Direct/Indirect 364	Direct/Indirect

FIXTURE FINISH







White

CANOPY FINISH







White

Black Metallic Textured Silver Metallic Textured

Black Metallic Textured ¹ Silver Metallic Textured

¹ Black Metallic Textured is only available with direct lumens of 300 lm/ft and 500 lm/ft.

ACOUSTIC PANEL COLOR



Acoustic panels exceeding 48" will have one seam. All other dimensions will be seamless.

For accompanying non-illuminating acoustic panels, see our Acoustic Circles, Quads, Triangles, and Ellipse spec pages.

Contact factory for larger sizes and additional colors.

APPROVALS













PERFORMANCE DATA

DIRECT (WHITE/SILVER METALLIC TEXTURED) DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW
	700 500 300	12 8 5	61 66 73
DIRECT (BLACK METALLIC TEXTURED) DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW
	500	12 8	38 41
INDIRECT (WHITE/SILVER METALLIC TEXTURED) OPAL (UD2)	LUMEN/FT	WATT/FT	LPW
	900 700 500 300	9 7 4 3	84 89 98 100

INDIRECT (BLACK METALLIC TEXTURED) OPAL (UD2)	LUMEN/FT	WATT/FT	LPW
	900	11	60
	700	9	63
	500	6	68
	300	3	74

DIMENSIONAL DIAGRAMS

