

KIORA I™ FULL SPECIFICATION SHEET



Fixture Type	Fixture Code	Quantities

1 DESCRIPTION

KIORA's neutral conical form with the opal diffused lens offers a minimalist decorative pendant that is versatile for a spectrum of space designs. The hidden internal reflector boosts the luminaire efficacy, delivering high light outputs suitable for high ceilings. The injection-moulded clear acrylic outer lens, coupled with the opal acrylic internal lens and a frosted aluminum reflector gives the fixture a timeless look with refinement at its core.

2 OPTICS & FEATURES







Declare

3 APPROVALS











4 GENERAL SPECIFICATION

OUTER LENS

Injection moulded opal acrylic with an etched lower band.

SUSPENSION

Single stainless steel cable.

INTERNAL LENS

Injection moulded clear acrylic.

POWER CABLE

Silver braided.



DRIVERS

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard. The driver is integral to the fixture canopy.

REFLECTOR

Aluminum, frosted finish with vertical facets.

REMOTE

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

SENSORS

Consult factory regarding sensor compatibility.

APPROVALS

Damp location, (Indoor use only).

5

HOW TO ORDER

1. LUMINAIRE

441202 2070 lms

2. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI)

40 4000K (min 80 CRI)

3. OPTIONS

RE Remote Emergency 3 347V (not available with RE)

6 TECHNICAL DATA

LUMINAIRE

 Code
 441202

 Power (LED)
 30W

 Delivered Ims
 2070

 LPW
 77

 Weight
 17.6lb

MECHANICAL

Mounts directly to a junction box (by others). Mounting hardware (by others - North America only).

CANOPY FINISH

White powder coated paint.

DELIVERED LUMENS

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

REPORTED L70 @25°C(77°F)

> 50,000 hrs.

DIMENSIONAL DIAGRAMS

