

# KIORA II DISC™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:

# KIORA II DISC™ - SUSPENDED

## GENERAL SPECIFICATION

### Diffuser

Injection moulded opal acrylic with an etched lower band.

### Power cable

Silver braided.

### Finish

Silver Metallic powder coated paint.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

### Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency luminaires have a 50mm/2" extended ballast housing. Not available with a 347V supply.

### Mechanical

Mounts directly to a junction box (by others - North America only). Mounting hardware (by others).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

### Suspension

Twin stainless steel cables.

### Disc

Aluminum plate.

### Reflector (optional)

Aluminum, frosted finish with vertical facets.

### Emergency systems


### Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### L70 @25°C (77°F)

> 50,000 hrs.

## OPTICS & FEATURES



Suspended Direct

# KIORA II DISC™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**441101** 44 1101

### B. CCT

**30** 3000K (min 80 CRI)                      **35** 3500K (min 80 CRI)                      **40** 4000K (min 80 CRI)

### C. DISC FINISH

**WH** White                      **BL** Blue                      **MS** Silver Metallic                      **OT** Other Painted Finish (RAL number required)

### D. DIMMING

**L2** Hi-Lume 1% EcoSystem

### E. OPTIONS

**RF** Internal Faceted Reflector                      **RE** Remote Emergency                      **3** 347V

# KIORA II DISC™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

Code	441101
Power (LED)	30W
Delivered lms	2087
LPW	78
Weight	24lb

---

## APPROVALS



# KIORA II DISC™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

