

KIORA II DISC™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:

KIORA II DISC™ - SUSPENDED

GENERAL SPECIFICATION

Lens

Injection moulded opal acrylic with an etched lower band.

Power cable

Silver braided.

Finish

Silver Metallic powder coated paint.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency luminaires have a 50mm/2" extended ballast housing. Not available with a 347V supply.

Mechanical

Mounts directly to a junction box (by others - North America only). Mounting hardware (by others).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

Suspension

Twin stainless steel cables.

Disc

Aluminum plate.

Reflector (optional)

Aluminum, frosted finish with vertical facets.

Emergency systems

Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

L70 @25°C (77°F)

> 50,000 hrs.

OPTICS & FEATURES



Suspended Direct

KIORA II DISC™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

441101 44 1101

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. DISC FINISH

WH White

BL Blue

MS Silver Metallic

OT Other Painted Finish (RAL number required)

D. DIMMING

L2 Hi-Lume 1% EcoSystem

E. OPTIONS

RF Internal Faceted Reflector

RE Remote Emergency

3 347V



KIORA II DISC™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	441101
Power (LED)	30W
Delivered lms	2087
LPW	78
Weight	24lb

APPROVALS



IP20



KIORA II DISC™ - SUSPENDED

DIMENSIONAL DIAGRAMS

