

KIORA II™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



KIORA II™ - SUSPENDED



KIORA II™ - SUSPENDED

KIORA's neutral conical form with opal diffuser offers a minimalist decorative pendant that is versatile for a spectrum of space designs. The hidden internal reflector boosts the luminaire efficacy, delivering high light outputs suitable for high ceilings.

GENERAL SPECIFICATION

Diffuser

Injection moulded opal acrylic with an etched lower band.

Power cable

Silver braided.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard. The driver is integral to the fixture housing.

Decorative disc/ring

6mm/0.25" green tint, clear acrylic with a polished edge and an etched face.

Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Sensors

Consult factory regarding sensor compatibility.

Approvals

Damp location, (Indoor use only).

Suspension

Twin stainless steel cables.

Finish

Silver Metallic powder coated paint. Other finishes available, consult factory.

Mechanical

Mounts directly to a junction box (by others - North America only). Mounting hardware (by others).

Reflector (optional)

Aluminum, frosted finish with vertical facets.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

Reported L70 @25°C (77°F)

> 50,000 hrs.


MOUNTING & OPTICS



Suspended Direct/Indirect



Direct-indirect



Declare.

KIORA II™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

441001 2070 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. CRADLE ARMS (OPTIONAL NOT REQUIRED)

C1 Cradle Arms with Disc

C2 Cradle Arms with Ring

D. OPTIONS

RF Internal Faceted Reflector

E. OPTIONS

RE Remote Emergency

3 347V (not available with RE)



KIORA II™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	441001
Power (LED)	30W
Delivered lms	2070
LPW	77
Weight	17.6lb

APPROVALS



KIORA II™ - SUSPENDED

DIMENSIONAL DIAGRAMS

