Project Name: Fixture Type:

Fixture Code: Quantities:











**KIORA's** neutral conical form with opal diffuser offers a minimalist decorative pendant that is versatile for a spectrum of space designs. The hidden internal reflector boosts the luminaire efficacy, delivering high light outputs suitable for high ceilings.

## **GENERAL SPECIFICATION**

#### **Outer Lens**

Injection moulded clear acrylic with an etched lower band.

## Suspension

Single stainless steel cable.

#### **Drivers**

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard. The driver is integral to the fixture canopy.

## Reflector

Aluminum, frosted finish with vertical facets.

## Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15′. Test switch fits a single gang box (not supplied).

#### Sensors

Consult factory regarding sensor compatibility.

## **Approvals**

Damp location, (Indoor use only).

# **OPTICS & FEATURES**







Direct-indirect



Declare

## Internal Lens

Injection moulded opal acrylic.

## Power cable

Silver braided.

#### Mechanical

Mounts directly to a junction box (by others). Mounting hardware (by others - North America only).

# Canopy finish

White powder coated paint.

## **Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

# Reported L70 @25°C (77°F)

> 50,000 hrs.

# **HOW TO ORDER**

## **A. LUMINAIRE**

**441201** 2290 lms

B. CCT

**30** 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

**C. OPTIONS** 

**RE** Remote Emergency 3 347V (not available with RE)

# **TECHNICAL DATA**

# **LUMINAIRE**

Code 441201 Power (LED) 30W **Delivered Ims** 2290 LPW 76 Weight 17.6lb

# **APPROVALS**









# **DIMENSIONAL DIAGRAMS**

