

KIORA™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



KIORA™ - SUSPENDED



KIORA™ - SUSPENDED

KIORA's neutral conical form with opal diffuser offers a minimalist decorative pendant that is versatile for a spectrum of space designs. The hidden internal reflector boosts the luminaire efficacy, delivering high light outputs suitable for high ceilings.

GENERAL SPECIFICATION

Outer diffuser

Injection moulded clear acrylic with an etched lower band.

Suspension

Single stainless steel cable.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard. The driver is integral to the fixture canopy.

Reflector

Aluminum, frosted finish with vertical facets.

Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Sensors

Consult factory regarding sensor compatibility.

Approvals

Damp location, (Indoor use only).

Internal diffuser

Injection moulded opal acrylic.

Power cable

Silver braided.

Mechanical

Mounts directly to a junction box (by others). Mounting hardware (by others - North America only).

Canopy finish

White powder coated paint.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


Reported L70 @25°C (77°F)

> 50,000 hrs.

OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect



Declare



KIORA™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

441201 2290 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. OPTIONS

RE Remote Emergency **3** 347V (not available with RE)

TECHNICAL DATA

LUMINAIRE

Code	441201
Power (LED)	30W
Delivered lms	2290
LPW	76
Weight	17.6lb

APPROVALS



KIORA™ - SUSPENDED

DIMENSIONAL DIAGRAMS

