

# KIORA™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



KIORA™ - SUSPENDED



# KIORA™ - SUSPENDED

KIORA's neutral conical form with opal diffuser offers a minimalist decorative pendant that is versatile for a spectrum of space designs. The hidden internal reflector boosts the luminaire efficacy, delivering high light outputs suitable for high ceilings.

## GENERAL SPECIFICATION

### Outer diffuser

Injection moulded clear acrylic with an etched lower band.

### Suspension

Single stainless steel cable.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard. The driver is integral to the fixture canopy.

### Reflector

Aluminum, frosted finish with vertical facets.

### Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Sensors

Consult factory regarding sensor compatibility.

### Approvals

Damp location, (Indoor use only).

### Internal diffuser

Injection moulded opal acrylic.

### Power cable

Silver braided.

### Mechanical

Mounts directly to a junction box (by others). Mounting hardware (by others - North America only).

### Canopy finish

White powder coated paint.


### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


### Reported L70 @25°C (77°F)

> 50,000 hrs.


## MOUNTING & OPTICS



Suspended Direct/Indirect



Direct-indirect



Declare

# KIORA™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**441201** 2290 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. OPTIONS

**RE** Remote Emergency

**3** 347V (not available with RE)

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>441201</b>
<b>Power (LED)</b>	30W
<b>Delivered lms</b>	2290
<b>LPW</b>	76
<b>Weight</b>	17.6lb

---

## APPROVALS



IP20



# KIORA™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

