

KURL™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

KURC1C42 42" radius, 8200 lms

KURC1C48 48" radius, 8900 lms

KURC1C54 54" radius, 10100 lms

KURC1C72 72" radius, 10300 lms

Data shown at max delivered lumens.

Recommended for installation on a hard ceiling.

B. LUMENS/FT

LPF055 550 lm/ft¹

LPF082 825 lm/ft²

LPF110 1100 lm/ft³

¹ Based on 50% of total output

² Based on 75% of total output.

³ 100% of total output.

C. CRI

CR80 CRI 80+

CR90 CRI 90+

D. CCT

CTA30 3000K

CTA35 3500K

CTA40 4000K

CTA50 RGBW

E. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V²

V4 Low Voltage³

¹ Not available in North America.

² Available with DA01 dimming only.

F. DIMMING

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1%¹

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

DA30 DSI/switchDim^{1 2}

DA40 DMX Dimming^{1 4}

DA45 PoE

¹ Not available with V3.

² Not available in North America.

³ Available with V4 only.

⁴ Available with CTA50 only.

G. FIXTURE FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA27 Wood grain - Light Cherry¹

FA28 Wood grain - Dark Walnut¹

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

¹ Longer lead times may apply, consult factory.

H. EMERGENCY

E0 Not required

E1 Emergency system - Integral¹

¹ Not available with V3.



KURL™ - CEILING

DIMENSIONAL DIAGRAMS

