
LE LOUVRE SYSTEMS™

FULL SPECIFICATION SHEET



FIXTURE TYPE	FIXTURE CODE	QUANTITIES

1 DESCRIPTION

The striking new concept in louver technology is disrupting the linear lighting category, and taking glare control to new heights. The **LE LOUVRE's** award-winning design with diagonal cross-hatched construction of the louver in a soft concave shape provides not just visual comfort but a touch of panache unseen in traditional linear lighting. Louvers are available in white for higher performance, black for the highest glare control, and rich satinized finishes - chrome, gold, champagne, for elegant interior designs. Build a continuous lighting plan with the new **LE LOUVRE SYSTEMS** option.


2 OPTICS & FEATURES


Suspended Direct


Suspended Direct/Indirect


Direct


Indirect UD1


Indirect UD3



Bios



Declare



PoE

3 APPROVALS



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

4 GENERAL SPECIFICATION

BODY
Aluminum.

FINISH
Powder coated

SUSPENSION
Steel cables.

POWER CABLE
Silver braided.

POE
Can be integrated into your data network via Power over Ethernet (PoE) connectivity.

BIOS
For circadian lighting, consult factory.

DRIVERS
HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

LENS
Opal acrylic. 2.4" width.

DELIVERED LUMENS
Delivered lumens & LPW based on 4000K CRI 80+

MECHANICAL
Luminaires mount directly over J box (by others).

REPORTED L70 @25°C (77°F)
> 60,000 hrs @ 2000 lumens/ft (6000 lumens/m)

ESTIMATED L70 @25°C (77°F)
> 165,000 hrs @ 2000 lumens/ft (6000 lumens/m)

INTEGRAL EMERGENCY SYSTEM(E1)
Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply. Refer to the Emergency option notes below for wattage, configuration and regional details.

LUMINAIRE LEVEL LIGHTING CONTROLS
This product can be configured for integration with luminaire-level lighting controls. Contact the factory for available options and project-specific requirements.

TUNABLE WHITE
Tunable White range from 2700K to 6500K is available; contact the factory for details.

RGBW
RGBW available, consult factory.

APPROVALS
Damp Rated.

DESIGNED BY
Serge Cornelissen.

DESIGN
US Pat. No. D959,043.

SEISMIC BRACING
Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

SUSTAINABILITY

Designed for on-site LED board, driver, and optic replacement.
Contact the factory for maintenance documentation.


© 2026 Beta-Calco Inc. Specifications are subject to change without notice

5 DESIGN OPTIONS

LOUVER

Frosted


Black


Satin Chrome


Satin Gold


Satin Champagne

FINISH

White - Textured


Black Metallic - Textured


Silver Metallic - Textured


Gold Metallic - Textured


Wood grain - Light Cherry [1]


Wood grain - Dark Walnut [1]


Wood grain - White Oak [1]


Midnight Blue Metallic - Textured


Copper Metallic


Charcoal Metallic - Textured


Bronze Metallic - Textured


Champagne Metallic


Red Metallic - Textured

[1] Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

CANOPY FINISH

White



Black Metallic - Textured


Silver Metallic - Textured


Gold Metallic - Textured


Midnight Blue Metallic - Textured


Copper Metallic


Charcoal Metallic - Textured


Bronze Metallic - Textured


Champagne Metallic


Red Metallic - Textured

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

6 HOW TO ORDER

Choose a Module

Make a selection from one of the following 7 sections. One power cord for every 50 linear feet. Connection parts for each section are shipped separately for on site assembly. Project drawings are not required for this product.

STRAIGHT SECTION 2FT

LE1PSL02 2ft middle section Direct
LE1PSM02 2ft middle section with power cord Direct
LE1PSN02 2ft section with end cap Direct
LE1PSP02 2ft section with end cap and power cord Direct

Available as Direct only.

STRAIGHT SECTION 4FT

LE1PSL04 4ft middle section Direct
LE1PSM04 4ft middle section with power cord Direct
LE1PSN04 4ft section with end cap Direct
LE1PSP04 4ft section with end cap and power cord Direct
LE2PSL04 4ft middle section Direct/Indirect
LE2PSM04 4ft middle section with power cord Direct/Indirect
LE2PSN04 4ft section with end cap Direct/Indirect
LE2PSP04 4ft section with end cap and power cord Direct/Indirect

STRAIGHT SECTION 6FT

LE1PSL06 6ft middle section Direct
LE1PSM06 6ft middle section with power cord Direct
LE1PSN06 6ft section with end cap Direct
LE1PSP06 6ft section with end cap and power cord Direct
LE2PSL06 6ft middle section Direct/Indirect
LE2PSM06 6ft middle section with power cord Direct/Indirect
LE2PSN06 6ft section with end cap Direct/Indirect
LE2PSP06 6ft section with end cap and power cord Direct/Indirect

STRAIGHT SECTION 8FT

LE1PSL08 8ft middle section Direct
LE1PSM08 8ft middle section with power cord Direct
LE1PSN08 8ft section with end cap Direct
LE1PSP08 8ft section with end cap and power cord Direct
LE2PSL08 8ft middle section Direct/Indirect
LE2PSM08 8ft middle section with power cord Direct/Indirect
LE2PSN08 8ft section with end cap Direct/Indirect
LE2PSP08 8ft section with end cap and power cord Direct/Indirect

STRAIGHT SECTION 10FT

LE1PSL10 10ft middle section Direct
LE1PSM10 10ft middle section with power cord Direct
LE1PSN10 10ft section with end cap Direct
LE1PSP10 10ft section with end cap and power cord Direct
LE2PSL10 10ft middle section Direct/Indirect
LE2PSM10 10ft middle section with power cord Direct/Indirect
LE2PSN10 10ft section with end cap Direct/Indirect
LE2PSP10 10ft section with end cap and power cord Direct/Indirect

STRAIGHT SECTION 12FT

LE1PSL12 12ft middle section Direct
LE1PSM12 12ft middle section with power cord Direct
LE1PSN12 12ft section with end cap Direct
LE1PSP12 12ft section with end cap and power cord Direct
LE2PSL12 12ft middle section Direct/Indirect
LE2PSM12 12ft middle section with power cord Direct/Indirect
LE2PSN12 12ft section with end cap Direct/Indirect
LE2PSP12 12ft section with end cap and power cord Direct/Indirect

CORNER SECTION (28"X28" L SHAPE)

LE1PSL01 Corner with no end caps Direct
LE1PSM01 Corner middle with power cord Direct
LE1PSN01 Corner with Left end cap Direct
LE1PSN03 Corner with Right end cap Direct
LE1PSP01 Corner with Left end cap and power cord Direct
LE1PSP03 Corner with Right end cap and power cord Direct
LE2PSL01 Corner with no end caps Direct/Indirect
LE2PSM01 Corner middle with power cord Direct/Indirect
LE2PSN01 Corner with Left end cap Direct/Indirect
LE2PSN03 Corner with Right end cap Direct/Indirect
LE2PSP01 Corner with Left end cap and power cord Direct/Indirect
LE2PSP03 Corner with Right end cap and power cord Direct/Indirect

LOUVER

LV1 Frosted
LV2 Black
LV4 Satin Chrome
LV6 Satin Gold
LV9 Satin Champagne

LM/FT (DIRECT)

LPF010 100 lm/ft
LPF020 200 lm/ft
LPF030 300 lm/ft
LPF040 400 lm/ft
LPF050 500 lm/ft
LPF060 600 lm/ft
LPF070 700 lm/ft
LPF080 800 lm/ft
LPF100 1000 lm/ft
LPF120 1200 lm/ft

Lumens/ft are determined by the color of the Louver. Consult website for available lumens/ft. based on selected louver.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

LM/FT (INDIRECT)

LPG000 Not required
LPG025 250 lm/ft
LPG050 500 lm/ft
LPG075 750 lm/ft
LPG100 1000 lm/ft
LPG120 1200 lm/ft
LPG160 1600 lm/ft

Consult website for available lumens/ft. All data shown based on DD3 diffuser.

CRI

CR80 CRI 80+
CR90 CRI 90+

CCT (DIRECT)

CTA30 3000K
CTA35 3500K
CTA40 4000K

CCT (INDIRECT)

CTB00 Not required
CTB30 3000K
CTB35 3500K
CTB40 4000K

DIRECT LENS

DD1 Asymmetric [1]
DD4 Comfort

[1] Recommended for use with Frosted louver only. When standing at the end view of the profile on the side where the power cord is installed, the asymmetric beam will aim to the right.

INDIRECT LENS

UD0 Not required
UD1 Batwing
UD3 Asymmetric diffuser [1]
UD4 Extra Wide Batwing [1]

[1] Available up to 1200 lm/ft.

BLACKOUT PLATE

UB00 Not required
UB_ _ Blackout plate [1]

[1] Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

VOLTAGE

V1 120/277V
V2 240V [1]
V3 347V [2]
V4 Low Voltage [3]

[1] Not available in North America. [2] Only available with DA01 dimming. [3] Only available with DA45 dimming.

DIMMING

DA01 0-10V Dimming 1.0%
DA02 0-10V Dimming 0.1% [1]
DA20 DALI Dimming 0.1% [1]
DA21 DALI Dimming 1.0% [1]
DA30 DSI/switchDim [2]
DA45 PoE [3]

[1] Not available with 347V. [2] Not available in North America. [3] Only available with V4.

CEILING TYPE

G1 Grid ceiling [1]
H1 Hard ceiling [2]

The cost for the canopies, power cables, connections mechanisms and endcaps for the fixture has been added to these items.
[1] Combo kit provided includes installation to T-bar and through tile mount. [2] Designed for drywall ceilings.

SUSPENSION

HLA03 3ft cable suspension
HLA06 6ft cable suspension
HLA09 9ft cable suspension

FIXTURE FINISH

FA01 White - Textured
FA02 Black Metallic - Textured
FA20 Silver Metallic - Textured
FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry [1]
FA28 Wood grain - Dark Walnut [1]
FA30 Wood grain - White Oak [1]
FA44 Midnight Blue Metallic - Textured
FA45 Copper Metallic
FA46 Charcoal Metallic - Textured
FA47 Bronze Metallic - Textured
FA52 Champagne Metallic
FA53 Red Metallic - Textured

[1] Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

CANOPY FINISH

CF01 White
CF02 Black Metallic - Textured
CF20 Silver Metallic - Textured
CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured
CF45 Copper Metallic
CF46 Charcoal Metallic - Textured
CF47 Bronze Metallic - Textured
CF52 Champagne Metallic
CF53 Red Metallic - Textured

EMERGENCY

E0 Not required
E1 Emergency system - Integral [1] [2]
E3 Emergency generator circuit [1] [2]

[1] Specify quantity of emergency sections or emergency generator circuits required based off total length of run. Not available with 347V.

[2] For North America, the minimum emergency system wattage is 10W. Refer to the fixture's lumens per watt to estimate emergency light output. The emergency system typically powers only a portion of the fixture, depending on the fixture configuration and number of drivers. Consult factory for emergency system configuration and illuminated section details.
For Europe, the emergency system wattage and configuration may vary. Consult factory for details.

Note: A drawing will be required at the time of ordering to determine the required location of the emergency sections or generator circuits.

CIRCUITS

CS1 Single circuit
CS2 Dual circuit [1]

[1] Independent control of uplight for LELP2P.


SENSORS

This product can be configured for integration with luminaire-level lighting controls. Contact the factory for available options and project-specific requirements.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice


7 PERFORMANCE DATA

DIRECT FROSTED LOUVER WITH COMFORT LENS (DD4)




LUMEN/FT	WATT/FT	LPW
1200	13	101
1000	9	107
800	7	109
700	6	111
600	5	115
500	4	115
400	3	115
300	3	116
200	2	121

DIRECT BLACK LOUVER WITH COMFORT LENS (DD4)




LUMEN/FT	WATT/FT	LPW
500	13	40
400	9	42
300	7	43
200	5	45
100	2	47

DIRECT SATIN CHROME LOUVER WITH COMFORT LENS (DD4)




LUMEN/FT	WATT/FT	LPW
800	13	60
700	11	60
600	9	63
500	7	65
400	5	68
300	3	68
200	3	68
100	2	69

DIRECT SATIN GOLD LOUVER WITH COMFORT LENS (DD4)




LUMEN/FT	WATT/FT	LPW
800	13	59
700	11	59
600	9	62
500	7	63
400	5	66
300	3	66
200	3	66
100	2	68

DIRECT SATIN CHAMPAGNE LOUVER WITH COMFORT LENS (DD4)




LUMEN/FT	WATT/FT	LPW
800	13	60
700	11	60
600	9	63
500	7	65
400	5	68
300	3	68
200	3	68
100	2	69

INDIRECT BATWING (UD1)



LUMEN/FT	WATT/FT	LPW
1600	13	129
1200	9	137
1000	7	140
750	5	146
500	3	147
250	2	152

INDIRECT ASYMMETRIC (UD3)




LUMEN/FT	WATT/FT	LPW
1200	13	97
1000	10	100
750	8	103
500	5	107
250	2	112

© 2026 Beta-Calco Inc. Specifications are subject to change without notice


8 TM-30 DATA

CCT 2700K




CRI(Ra)	93
CRI(R9)	61
TM30(Rf)	91
TM30(Rg)	98
Duv	-0.0022

CCT 3000K




CRI(Ra)	92
CRI(R9)	58
TM30(Rf)	92
TM30(Rg)	100
Duv	-0.0003

CCT 3500K



CRI(Ra)	91
CRI(R9)	53
TM30(Rf)	90
TM30(Rg)	99
Duv	-0.0007


CCT 4000K




CRI(Ra)	93
CRI(R9)	64
TM30(Rf)	90
TM30(Rg)	98
Duv	0.0000


© 2026 Beta-Calco Inc. Specifications are subject to change without notice


9 DIMENSIONAL DIAGRAMS





ISOMETRIC TOP VIEW





ISOMETRIC BOTTOM VIEW

© 2026 Beta-Calco Inc. Specifications are subject to change without notice