

LE LOUVRE™ - CONTINUOUS WALL

Project Name:



Fixture Type:

Fixture Code:

Quantities:



LE LOUVRE™ - CONTINUOUS WALL



LE LOUVRE™ - CONTINUOUS WALL

The striking new concept in louver technology is disrupting the linear lighting category, and taking glare control to new heights. Our award-winning design with diagonal cross-hatched construction of the louver in a soft concave shape provides not just visual comfort but a touch of panache unseen in traditional linear lighting. Louvers are available in white for higher performance, black for the highest glare control, and rich satinized finishes - chrome, gold, champagne, for elegant interior designs.

GENERAL SPECIFICATION

Body

Aluminum.

Drivers

HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

PoE

Can be integrated into your data network via Power over Ethernet (PoE) connectivity.

Delivered lumens

Delivered lumens & LPW based on 4000K CRI 80+

Integral Emergency system

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

Reported L70 @25°C (77°F)

> 60,000 hrs @ 2000 lumens/ft (6000 lumens/m)

Tunable White

Tunable white available, consult factory.

Designed by

Serge Cornelissen.

Finish

Powder coated

Diffuser

Opal acrylic.

BIOS

For circadian lighting, consult factory.

Mechanical

Luminaires mount directly over J box (by others).

Sensors

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.

Estimated L70 @25°C (77°F)

> 165,000 hrs @ 2000 lumens/ft (6000 lumens/m)

Approvals

Damp Rated.


Design

US Pat. No. D959,043.


MOUNTING & OPTICS



Wall - up/down



Indirect UD2




Indirect UD3



Direct DD4



Bios



Declare



PoE



LE LOUVRE™ - CONTINUOUS WALL

HOW TO ORDER

A. LUMINAIRE

LELW1W Direct

LELW2W Direct/Indirect

One power cord for every 50 linear feet.

B. LENGTH OF RUN

SFA _ _ _

The minimum length of order is 4ft. Lengths are to be in 2ft increments.

Example: 4ft = SFA040

Example: 10ft = SFA100

Example: 50ft = SFA500

For runs over 50ft in length, consult factory.

C. MAX LENGTH PER SECTION

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4 10ft segments. For special requirements, please contact sales@betacalco.com.

D. LOUVER

LV1 Frosted

LV2 Black

LV4 Satin Chrome

LV6 Satin Gold ¹

LV9 Satin Champagne ¹

¹ There will be a slight color cast on the wall when using the Satin Gold or Satin Champagne louvers.

E. LM/FT (DIRECT)

LPF010 100 lm/ft

LPF020 200 lm/ft

LPF030 300 lm/ft

LPF040 400 lm/ft

LPF050 500 lm/ft

LPF060 600 lm/ft

LPF070 700 lm/ft

LPF080 800 lm/ft

LPF100 1000 lm/ft

LPF120 1200 lm/ft

Lumens/ft are determined by the color of the Louver. Consult website for available lumens/ft. based on selected louver.

F. LM/FT (INDIRECT)

LPG000 Not required

LPG025 250 lm/ft

LPG050 500 lm/ft

LPG075 750 lm/ft

LPG100 1000 lm/ft

LPG120 1200 lm/ft

LPG160 1600 lm/ft

Consult website for available lumens/ft based on selected louvers.

G. CRI

CR80 CRI 80+

CR90 CRI 90+

H. CCT (DIRECT)

CTA30 3000K

CTA35 3500K

CTA40 4000K

I. CCT (INDIRECT)

CTB00 Not required

CTB30 3000K

CTB35 3500K

CTB40 4000K



LE LOUVRE™ - CONTINUOUS WALL

J. DIRECT DIFFUSER

DD1 Asymmetric diffuser ¹ **DD4** Comfort diffuser

¹ Recommended for use with Frosted louver only. When standing at the end view of the profile on the side where the power cord is installed, the asymmetric beam will aim to the right.

K. UPLIGHT DIFFUSER

UD0 Not required **UD2** Opal diffuser **UD3** Asymmetric diffuser ¹

¹ Available up to 1200 lm/ft. The asymmetric distribution will be directed away from the wall.

L. BLACKOUT PLATE

UB00 Not required **UB_ _** Blackout plate ¹

¹ Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

M. VOLTAGE

V1 120/277V **V2** 240V ¹ **V3** 347V ² **V4** Low Voltage ³

¹ Not available in North America.

² Only available with DA01 dimming.

³ Only available with DA45 dimming.

N. DIMMING

DA01 0-10V Dimming 1.0% **DA02** 0-10V Dimming 0.1% ¹ **DA20** DALI Dimming 0.1% ¹ **DA21** DALI Dimming 1.0% ¹
DA30 DSI/switchDim ² **DA45** PoE ³

¹ Not available with 347V.

² Not available in North America.

³ Only available with V4.

O. FIXTURE FINISH

FA01 White **FA02** Black Metallic - Textured **FA20** Silver Metallic - Textured **FA25** Gold Metallic - Textured
FA27 Wood grain - Light Cherry ¹ **FA28** Wood grain - Dark Walnut ¹ **FA44** Midnight Blue Metallic - Textured **FA45** Copper Metallic
FA46 Charcoal Metallic - Textured **FA47** Bronze Metallic - Textured **FA52** Champagne Metallic **FA53** Red Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

P. EMERGENCY

EO Not required **E1** Emergency system - Integral **E3** Emergency generator circuit ¹

¹ A drawing will be required at time of ordering to determine the required number and location of the emergency sections or generator circuits. ¹ Available upon request, consult factory for details. Not available with 347V.

Q. CIRCUITS

CS1 Single circuit **CS2** Dual circuit ¹

R. SENSORS

LE LOUVRE™ - CONTINUOUS WALL


TECHNICAL DATA

LUMINAIRE

One power cord for every 50 linear feet.


Code	LELW1W	LELW2W
Light Direction	Direct	Direct/Indirect

LOUVER



¹ There will be a slight color cast on the wall when using the Satin Gold or Satin Champagne louvers.

FINISH



¹ Longer than normal lead times may apply, consult factory.

APPROVALS



LE LOUVRE™ - CONTINUOUS WALL


PERFORMANCE DATA

DIRECT FROSTED LOUVER WITH DIFFUSED LENS (DD3)

LUMEN/FT

WATT/FT

LPW



1200
1000
800
700
600
500
400
300
200

13
9
7
6
5
4
3
2


109
115
118
119
123
123
123
124
130

DIRECT BLACK LOUVER WITH DIFFUSED LENS (DD3)

LUMEN/FT

WATT/FT

LPW



500
400
300
200
100

13
9
7
5
2


43
45
46
48
50

DIRECT SATIN CHROME LOUVER WITH DIFFUSED LENS (DD3)

LUMEN/FT

WATT/FT

LPW



800
700
600
500
400
300
200
100

13
11
9
7
5
3
3
2

64
64
68
69
73
73
73
75


LE LOUVRE™ - CONTINUOUS WALL

DIRECT SATIN GOLD LOUVER WITH DIFFUSED LENS (DD3)

LUMEN/FT

WATT/FT

LPW



800
700
600
500
400
300
200
100

13
11
9
7
5
3
3
2


63
63
67
68
71
71
71
73

DIRECT SATIN CHAMPAGNE LOUVER WITH DIFFUSED LENS (DD3)

LUMEN/FT

WATT/FT

LPW



800
700
600
500
400
300
200
100

13
11
9
7
5
3
3
2


64
64
68
69
73
73
73
75

INDIRECT BATWING (UD1)

LUMEN/FT

WATT/FT

LPW



1600
1200
1000
750
500
250

13
9
7
5
3
2

129
137
140
146
147
152


LE LOUVRE™ - CONTINUOUS WALL

INDIRECT ASYMMETRIC (UD3)

LUMEN/FT

WATT/FT

LPW



1200
1000
750
500
250





13
10
8
5
2

97
100
103
107
112

LE LOUVRE™ - CONTINUOUS WALL

DIMENSIONAL DIAGRAMS

Isometric Views



Top View [Uplight]




Bottom View [Downlight]


LE LOUVRE™ - CONTINUOUS WALL

Wall Mount Configurations


4FT




6FT



8FT



10FT



12FT

