LE LOUVRE™

SHORT SPECIFICATION SHEET



FIXTURE TYPE	FIXTURE CODE	QUANTITIES

1 HOW TO ORDER

LUMINAIRE

LELP1P Direct
LELP2P Direct/Indirect

One power cord for every 50 linear feet.

LENGTH OF RUN

The minimum length of order is 4'. Lengths are to be in 2' increments. Example:
4' = SFA040, 10' = SFA100, 50' = SFA500
For runs over 50ft in length, consult factory.

SFA_ _ _

MAX LENGTH PER SECTION

SL04 4ft
SL06 6ft
SL08 8ft
SL10 10ft
SL12 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40' run is required and SL12 (12') is selected, we would provide 4 10' segments. For special requirements, please contact sales@betacalco.com.

LOUVER

LV1 Frosted
LV2 Black
LV4 Satin Chrome
LV6 Satin Gold
LV9 Satin Champagne

Refer to the performance data for the output specifications of each louver option.

LM/FT (DIRECT)

LPF010 100 lm/ft
LPF020 200 lm/ft
LPF030 300 lm/ft
LPF040 400 lm/ft
LPF050 500 lm/ft
LPF060 600 lm/ft
LPF070 700 lm/ft
LPF080 800 lm/ft
LPF100 1000 lm/ft
LPF120 1200 lm/ft

Lumens/ft are determined by the color of the Louver. Consult website for available lumens/ft. based on selected louver.

LM/FT (INDIRECT)

LPG000 Not required
LPG025 250 lm/ft
LPG050 500 lm/ft
LPG075 750 lm/ft
LPG100 1000 lm/ft
LPG120 1200 lm/ft
LPG160 1600 lm/ft

Consult website for available lumens/ft.
All data shown based on DD3 diffuser.

CRI

CR80 CRI 80+
CR90 CRI 90+

CCT (DIRECT)

CTA27 2700K
CTA30 3000K
CTA35 3500K
CTA40 4000K
CTA60 Tunable White

* If Tunable White is required, it needs to be selected for both direct and indirect. For other combinations, consult factory.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

LE LOUVRE™ - SUSPENDED CONTINUOUS
SHORT SPECIFICATION SHEET

CCT (INDIRECT)

CTB00 Not required
CTB27 2700K
CTB30 3000K
CTB35 3500K
CTB40 4000K
CTB60 Tunable White

* If Tunable White is required, it needs to be selected for both direct and indirect. For other combinations, consult factory.

DIRECT LENS

DD1 Asymmetric [1]
DD4 Comfort

[1] Recommended for use with Frosted louver only. When standing at the end view of the profile on the side where the power cord is installed, the asymmetric beam will aim to the right.

INDIRECT LENS

UD0 Not required
UD1 Batwing
UD3 Asymmetric [1]
UD4 Extra Wide Batwing [1]

[1] Available up to 1200 lm/ft.

BLACKOUT PLATE

UB00 Not required
UB_ _ Blackout plate [1]

[1] Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

VOLTAGE

V1 120/277V
V2 240V [1]
V3 347V [2]
V4 Low Voltage [3]

[1] Not available in North America. [2] Only available with DA01 dimming. [3] Only available with DA45 dimming.

DIMMING

DA01 0-10V Dimming 1.0%
DA02 0-10V Dimming 0.1% [1]
DA20 DALI Dimming 0.1% [1]
DA21 DALI Dimming 1.0% [1]
DA23 DALI DT8 Dimming 0.1% - Tunable White [1] [2]
DA45 PoE [3]

[1] Not available with V3.
[2] Only available with Tunable White.
[3] Only available with V4.

CEILING TYPE

G1 Grid ceiling [1]
H1 Hard ceiling [2]

The cost for the canopies, power cables, connections mechanisms and endcaps for the fixture has been added to these items.
[1] Combo kit provided includes installation to T-bar and through tile mount. [2] Designed for drywall ceilings.

SUSPENSION

HLA03 3ft cable suspension
HLA06 6ft cable suspension
HLA09 9ft cable suspension

FIXTURE FINISH

FA01 White - Textured
FA02 Black Metallic - Textured
FA20 Silver Metallic - Textured
FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry [1]
FA28 Wood grain - Dark Walnut [1]
FA30 Wood grain - White Oak [1]
FA44 Midnight Blue Metallic - Textured
FA45 Copper Metallic
FA46 Charcoal Metallic - Textured
FA47 Bronze Metallic - Textured
FA52 Champagne Metallic
FA53 Red Metallic - Textured

[1] Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

CANOPY FINISH

CF01 White
CF02 Black Metallic - Textured
CF20 Silver Metallic - Textured
CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured
CF45 Copper Metallic
CF46 Charcoal Metallic - Textured
CF47 Bronze Metallic - Textured
CF52 Champagne Metallic
CF53 Red Metallic - Textured

EMERGENCY

E0 Not required
E1 Emergency system - Integral [1] [2]
E3 Emergency generator circuit [1] [2]

[1] Specify quantity of emergency sections or emergency generator circuits required based off total length of run. Not available with 347V.

[2] For North America, the minimum emergency system wattage is 10W. Refer to the fixture's lumens per watt to estimate emergency light output. The emergency system typically powers only a portion of the fixture, depending on the fixture configuration and number of drivers. Consult factory for emergency system configuration and illuminated section details.
For Europe, the emergency system wattage and configuration may vary. Consult factory for details.

Note: A drawing will be required at the time of ordering to determine the required location of the emergency sections or generator circuits.

CIRCUITS

CS1 Single circuit
CS2 Dual circuit [1]

[1] Independent control of uplight for LELP2P.

SENSORS

This product can be configured for integration with luminaire-level lighting controls. Contact the factory for available options and project-specific requirements.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice