

# LE LOUVRE™ SHORT SPECIFICATION SHEET



Fixture Type	Fixture Code	Quantities

# 1

# HOW TO ORDER

#### 1. LUMINAIRE

LELP1P Direct LELP2P Direct/Indirect

One power cord for every 50 linear feet.

#### 2. LENGTH OF RUN

The minimum length of order is 4ft. Lengths are to be in 2ft increments.

Example: 4ft = SFA040 Example: 10ft = SFA100 Example: 50ft = SFA500

For runs over 50ft in length, consult factory.

#### SFA\_\_\_

The minimum length of order is 4ft. Lengths are to be in 2ft increments.

Example: 4ft = SFA040 Example: 10ft = SFA100 Example: 50ft = SFA500

For runs over 50ft in length, consult factory.

#### 3. MAX LENGTH PER SECTION

**SL04** 4ft **SL06** 6ft **SL08** 8ft **SL10** 10ft

**SL12** 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4 10ft segments. For special requirements, please contact sales@betacalco.com.

#### 4. LOUVER

LV1 Frosted LV2 Black LV4 Satin Chrome LV6 Satin Gold

LV9 Satin Champagne

Refer to the performance data for the output specifications of each louver option.

#### 5. LM/FT (DIRECT)

 LPF010 100 lm/ft
 LPF020 200 lm/ft
 LPF030 300 lm/ft
 LPF040 400 lm/ft

 LPF050 500 lm/ft
 LPF060 600 lm/ft
 LPF070 700 lm/ft
 LPF080 800 lm/ft

**LPF100** 1000 lm/ft **LPF120** 1200 lm/ft

Lumens/ft are determined by the color of the Louver. Consult website for available lumens/ft. based on selected louver.

#### 6. LM/FT (INDIRECT)

**LPG000** Not required **LPG025** 250 lm/ft **LPG050** 500 lm/ft **LPG075** 750 lm/ft

Consult website for available lumens/ft.
All data shown based on DD3 diffuser.

#### **7. CRI**

CR80 CRI 80+ CR90 CRI 90+

# 8. CCT (DIRECT)

#### 9. CCT (INDIRECT)

**CTB00** Not required **CTB27** 2700K **CTB30** 3000K **CTB35** 3500K

CTB40 4000K

#### 10. DIRECT LENS

DD1 Asymmetric <sup>1</sup> DD4 Comfort

#### 11. INDIRECT LENS

**UD0** Not required **UD1** Batwing **UD3** Asymmetric <sup>1</sup>

<sup>&</sup>lt;sup>1</sup> Recommended for use with Frosted louver only. When standing at the end view of the profile on the side where the power cord is installed, the asymmetric beam will aim to the right.

<sup>&</sup>lt;sup>1</sup> Available up to 1200 lm/ft.

**UB00** Not required **UB\_** Blackout plate <sup>1</sup>

<sup>1</sup> Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

# 13. VOLTAGE

**V1** 120/277V **V2** 240V <sup>1</sup> **V3** 347V <sup>2</sup> **V4** Low Voltage <sup>3</sup>

#### 14. DIMMING

**DA01** 0-10V Dimming 1.0% **DA02** 0-10V Dimming 0.1% <sup>1</sup> **DA20** DALI Dimming 0.1% <sup>1</sup> **DA21** DALI Dimming 1.0% <sup>1</sup>

DA30 DSI/switchDim <sup>2</sup> DA45 PoE <sup>3</sup>

# 15. CEILING TYPE

G1 Grid ceiling <sup>1</sup> H1 Hard ceiling <sup>2</sup>

The cost for the canopies, power cables, connections mechanisms and endcaps for the fixture has been added to these items.

#### 16. SUSPENSION

HLA03 3ft cable suspension HLA06 6ft cable suspension HLA09 9ft cable suspension

<sup>&</sup>lt;sup>1</sup> Not available in North America.

<sup>&</sup>lt;sup>2</sup> Only available with DA01 dimming.

<sup>&</sup>lt;sup>3</sup> Only available with DA45 dimming.

<sup>&</sup>lt;sup>1</sup> Not available with 347V.

<sup>&</sup>lt;sup>2</sup> Not available in North America.

<sup>&</sup>lt;sup>3</sup> Only available with V4.

<sup>&</sup>lt;sup>1</sup> Combo kit provided includes installation to T-bar and through tile mount.

<sup>&</sup>lt;sup>2</sup> Designed for drywall ceilings.

#### 17. FIXTURE FINISH

FA01 White - Textured FA20 Silver Metallic - Textured FA25 Gold Metallic - Textured FA26 Silver Metallic - Textured FA26 Metallic - Textured FA26 Silver Metallic - Textured FA26 Metallic - Textured FA26 Silver Metallic - T

FA27 Wood grain - Light Cherry <sup>1</sup> FA28 Wood grain - Dark Walnut <sup>1</sup>FA30 Wood grain - White Oak <sup>1</sup> FA44 Midnight Blue Metallic -

Textured

FA45 Copper Metallic FA46 Charcoal Metallic - FA47 Bronze Metallic - Textured FA52 Champagne Metallic

Textured

FA53 Red Metallic - Textured

#### 18. CANOPY FINISH

CF01 White CF02 Black Metallic - Textured CF20 Silver Metallic - Textured CF25 Gold Metallic - Textured

CF44 Midnight Blue Metallic -

CF45 Copper Metallic CF46 Charcoal Metallic -

CF47 Bronze Metallic - Textured

Textured Textured

CF52 Champagne Metallic CF53 Red Metallic - Textured

#### 19. EMERGENCY

E0 Not required E1 Emergency system - Integral <sup>1</sup> E3 Emergency generator circuit <sup>1</sup>

# **20. CIRCUITS**

CS1 Single circuit CS2 Dual circuit 1

#### 21. SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.

<sup>&</sup>lt;sup>1</sup> Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

<sup>&</sup>lt;sup>1</sup> A drawing will be required at the time of ordering to determine the required number and location of the emergency sections or generator circuits. <sup>1</sup> Available upon request, consult factory for details. Not available with 347V.

<sup>&</sup>lt;sup>1</sup> Independent control of uplight for LELP2P.