



LE LOUVRE™

SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 HOW TO ORDER

1. LUMINAIRE

LLELP1P Direct

LLELP2P Direct/Indirect

One power cord for every 50 linear feet.

2. LENGTH OF RUN

The minimum length of order is 4'. Lengths are to be in 2' increments. Example:

4' = SFA040, 10' = SFA100, 50' = SFA500

For runs over 50ft in length, consult factory.

SFA_ _ _

3. MAX LENGTH PER SECTION

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40' run is required and SL12 (12') is selected, we would provide 4 10' segments. For special requirements, please contact sales@betacalco.com.

4. LOUVER

| | | | |
|----------------------------|------------------|-------------------------|-----------------------|
| LV1 Frosted | LV2 Black | LV4 Satin Chrome | LV6 Satin Gold |
| LV9 Satin Champagne | | | |

Refer to the performance data for the output specifications of each louver option.

5. LM/FT (DIRECT)

| | | | |
|--------------------------|--------------------------|-------------------------|-------------------------|
| LPF010 100 lm/ft | LPF020 200 lm/ft | LPF030 300 lm/ft | LPF040 400 lm/ft |
| LPF050 500 lm/ft | LPF060 600 lm/ft | LPF070 700 lm/ft | LPF080 800 lm/ft |
| LPF100 1000 lm/ft | LPF120 1200 lm/ft | | |

Lumens/ft are determined by the color of the Louver. Consult website for available lumens/ft. based on selected louver.

6. LM/FT (INDIRECT)

| | | | |
|----------------------------|--------------------------|--------------------------|-------------------------|
| LPG000 Not required | LPG025 250 lm/ft | LPG050 500 lm/ft | LPG075 750 lm/ft |
| LPG100 1000 lm/ft | LPG120 1200 lm/ft | LPG160 1600 lm/ft | |

Consult website for available lumens/ft.
All data shown based on DD3 diffuser.

7. CRI

| | |
|---------------------|---------------------|
| CR80 CRI 80+ | CR90 CRI 90+ |
|---------------------|---------------------|

8. CCT (DIRECT)

| | | | |
|--------------------|--------------------|--------------------|--------------------|
| CTA27 2700K | CTA30 3000K | CTA35 3500K | CTA40 4000K |
|--------------------|--------------------|--------------------|--------------------|

9. CCT (INDIRECT)

| | | | |
|---------------------------|--------------------|--------------------|--------------------|
| CTB00 Not required | CTB27 2700K | CTB30 3000K | CTB35 3500K |
| CTB40 4000K | | | |

10. DIRECT LENS

| | |
|------------------------------------|--------------------|
| DD1 Asymmetric ¹ | DD4 Comfort |
|------------------------------------|--------------------|

¹ Recommended for use with Frosted louver only. When standing at the end view of the profile on the side where the power cord is installed, the asymmetric beam will aim to the right.

11. INDIRECT LENS

UD0 Not required **UD1** Batwing **UD3** Asymmetric ¹

¹ Available up to 1200 lm/ft.

12. BLACKOUT PLATE

UB00 Not required **UB_ _** Blackout plate ¹

¹ Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

13. VOLTAGE

V1 120/277V **V2** 240V ¹ **V3** 347V ² **V4** Low Voltage ³

¹ Not available in North America. ² Only available with DA01 dimming. ³ Only available with DA45 dimming.

14. DIMMING

DA01 0–10V Dimming 1.0% **DA02** 0–10V Dimming 0.1% ¹ **DA20** DALI Dimming 0.1% ¹ **DA21** DALI Dimming 1.0% ¹
DA30 DSI/switchDim ² **DA45** PoE ³

¹ Not available with 347V. ² Not available in North America. ³ Only available with V4.

15. CEILING TYPE

G1 Grid ceiling ¹ **H1** Hard ceiling ²

The cost for the canopies, power cables, connections mechanisms and endcaps for the fixture has been added to these items.

¹ Combo kit provided includes installation to T-bar and through tile mount. ² Designed for drywall ceilings.

16. SUSPENSION

HLA03 3ft cable suspension **HLA06** 6ft cable suspension **HLA09** 9ft cable suspension

17. FIXTURE FINISH

| | | | |
|----------------------------------------------------|---------------------------------------------------|-------------------------------------------------|-----------------------------------------------|
| FA01 White – Textured | FA02 Black Metallic – Textured | FA20 Silver Metallic – Textured | FA25 Gold Metallic – Textured |
| FA27 Wood grain – Light Cherry ¹ | FA28 Wood grain – Dark Walnut ¹ | FA30 Wood grain – White Oak ¹ | FA44 Midnight Blue Metallic – Textured |
| FA45 Copper Metallic | FA46 Charcoal Metallic – Textured | FA47 Bronze Metallic – Textured | FA52 Champagne Metallic |
| FA53 Red Metallic – Textured | | | |

¹ Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

18. CANOPY FINISH

| | | | |
|-----------------------------------------------|---------------------------------------|------------------------------------------|----------------------------------------|
| CF01 White | CF02 Black Metallic – Textured | CF20 Silver Metallic – Textured | CF25 Gold Metallic – Textured |
| CF44 Midnight Blue Metallic – Textured | CF45 Copper Metallic | CF46 Charcoal Metallic – Textured | CF47 Bronze Metallic – Textured |
| CF52 Champagne Metallic | CF53 Red Metallic – Textured | | |

19. EMERGENCY

| | | |
|------------------------|----------------------------------------------------|----------------------------------------------------|
| E0 Not required | E1 Emergency system – Integral ¹ | E3 Emergency generator circuit ¹ |
|------------------------|----------------------------------------------------|----------------------------------------------------|

¹ A drawing will be required at the time of ordering to determine the required number and location of the emergency sections or generator circuits. Available upon request, consult factory for details. Not available with 347V.

20. CIRCUITS

| | |
|---------------------------|--------------------------------------|
| CS1 Single circuit | CS2 Dual circuit ¹ |
|---------------------------|--------------------------------------|

¹ Independent control of uplight for LELP2P.

21. SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.