

LPU SQ™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:

LPU SQ™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Extruded aluminum and steel.

Finish

Powder coated as specified.

Power cable

Silver braided.

Mechanical

Luminaire mounts directly over a junction box.

L70 @25°C (77°F)

> 50,000 hrs.

Suspension

Four cables.

Dust cover

Clear polycarbonate.

Drivers

HPF, electronic, 0-10V (EU-240V), 10% dimming standard.

Remote emergency system

Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

OPTICS & FEATURES



Suspended Direct

LPU SQ™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

773501 77 3501

773511 77 3511

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

MS Silver Metallic

OT Other Painted Finish (RAL number required)

D. DIMMING

DA DALI Drivers

DX DMX Drivers

E. OPTIONS

RE Remote Emergency (max distance 10 ft)

LPU SQ™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	773501	773511
Power (LED)	108W	226W
Delivered lms	13761	28365
LPW	127	126
Width (A)	32" SQ	32" SQ

APPROVALS



LPU SQ™ - SUSPENDED

DIMENSIONAL DIAGRAMS

