

# LPU SQ™ - SUSPENDED

---

Project Name:

Fixture Type:

---

Fixture Code:

Quantities:

# LPU SQ™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Extruded aluminum and steel.

### Finish

Powder coated as specified.

### Power cable

Silver braided.

### Mechanical

Luminaire mounts directly over a junction box.

### L70 @25°C (77°F)

> 50,000 hrs.

### Suspension

Four cables.

### Dust cover

Clear polycarbonate.

### Drivers

HPF, electronic, 0-10V (EU-240V), 10% dimming standard.

### Remote emergency system

Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

## OPTICS & FEATURES



Suspended Direct

# LPU SQ™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**773501** 77 3501

**773511** 77 3511

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MS** Silver Metallic

**OT** Other Painted Finish (RAL number required)

### D. DIMMING

**DA** DALI Drivers

**DX** DMX Drivers

### E. OPTIONS

**RE** Remote Emergency (max distance 10 ft)



# LPU SQ™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>773501</b>	<b>773511</b>
<b>Power (LED)</b>	108W	226W
<b>Delivered lms</b>	13761	28365
<b>LPW</b>	127	126
<b>Width (A)</b>	32" SQ	32" SQ

---

## APPROVALS



IP20

# LPU SQ™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

