

MACRO STRAIGHT™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



MACRO STRAIGHT™ - SUSPENDED



MACRO STRAIGHT™ - SUSPENDED

The robust 4" linear profile boasts above-average light output, ideal for general illumination at standard ceiling heights. An indirect light option is available with either a clear or opal diffuser. Available in 10 decorative finishes, as well as 2 wood grain finishes Light Cherry and Dark Walnut. Three color temperatures are available plus monochromatic red, green, and blue. **MACRO STRAIGHT** can integrate with your data network via Power over Ethernet.

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Diffusers

Opal polycarbonate, supplied in sections.

Integral emergency system

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

Drivers

Integral, HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

Delivered lumens

Delivered lumens & LPW based on 4000K (min 80 CRI) for white LEDs only.

Approvals

Damp Rated.

Finish

Polyester powder coated.

Power cable

Silver braided.

Suspension

Steel cables. Recommended minimum distance from ceiling: 12" (305mm) for white LEDs and 24" (610mm) for colored LEDs (only for direct/indirect).

Mechanical

Luminaires mount directly over J box (by others - North America only).

L70 @25°C (77°F)

> 60,000 hrs.

MOUNTING & OPTICS



Suspended Direct



Suspended Direct/Indirect



Declare



PoE



MACRO STRAIGHT™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

MCRP1P Direct

MCRP2P Direct/Indirect

LENGTH OF RUN

SFA_ _ _ _

Length of run is 3, 4, 5, 6, 7 or 8ft only, not available as a continuous run.

FIXTURE LENGTH

SL03 3ft

SL04 4ft

SL05 5ft

SL06 6ft

SL07 7ft

SL08 8ft

B. LUMENS/FT (DIRECT)

LPF028 285 lm/ft

LPF057 575 lm/ft

LPF085 850 lm/ft

LPF115 1150 lm/ft

C. LUMENS/FT (INDIRECT)

LPG00 Not required

LPG012 125 lm/ft

LPG025 250 lm/ft

LPG037 375 lm/ft

LPG050 500 lm/ft

D. CRI

CR80 CRI 80+

E. CCT DIRECT

CTA30 3000K

CTA35 3500K

CTA40 4000K

CTA54 Red

CTA55 Green

CTA56 Blue

CCT INDIRECT

CTB00 Not required

CTB30 3000K

CTB35 3500K

CTB40 4000K

CTB54 Red

CTB55 Green

CTB56 Blue

F. UPLIGHT DIFFUSER

UD0 Not required

UD1 Clear diffuser

UD2 Opal diffuser ¹

¹ 10% reduction on indirect lumens.

G. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Available with DA01 dimming only.

³ Only available with DA45 dimming.

H. DIMMING

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1% ¹

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% ¹

DA30 DSI/switchDim ²

DA45 PoE ³

¹ Not available with V3.

² Not available in North America.

³ Only available with V4.



MACRO STRAIGHT™ - SUSPENDED

I. FIXTURE FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry ¹	FA28 Wood grain - Dark Walnut ¹	FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic
FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic	FA53 Red Metallic - Textured

¹ Longer lead time may apply, consult factory.

J. CANOPY FINISH

CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured	CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured	CF47 Bronze Metallic - Textured
CF52 Champagne Metallic	CF53 Red Metallic - Textured		

K. EMERGENCY

E0 Not required	E1 Emergency system - Integral ¹
------------------------	--

¹ Direct illumination and 120/277V or 240V only.

L. CIRCUITS


CS1 Single circuit	CS2 Dual circuit
---------------------------	-------------------------

M. CONTROLS

CO Not required	C1 Encelium/Zigbee
------------------------	---------------------------


MACRO STRAIGHT™ - SUSPENDED

FIXTURE FINISH



¹ Longer lead time may apply, consult factory.

CANOPY FINISH



APPROVALS



MACRO STRAIGHT™ - SUSPENDED

DIMENSIONAL DIAGRAMS

