

MACRO STRAIGHT™ - SUSPENDED



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

MCRP1P Direct

MCRP2P Direct/Indirect

LENGTH OF RUN

SFA _ _ _ _

Length of run is 3, 4, 5, 6, 7 or 8ft only, not available as a continuous run.

FIXTURE LENGTH

SL03 3ft

SL04 4ft

SL05 5ft

SL06 6ft

SL07 7ft

SL08 8ft

B. LUMENS/FT (DIRECT)

LPF028 285 lm/ft

LPF057 575 lm/ft

LPF085 850 lm/ft

LPF115 1150 lm/ft

C. LUMENS/FT (INDIRECT)

LPG00 Not required

LPG012 125 lm/ft

LPG025 250 lm/ft

LPG037 375 lm/ft

LPG050 500 lm/ft

D. CRI

CR80 CRI 80+

E. CCT DIRECT

CTA30 3000K

CTA35 3500K

CTA40 4000K

CTA54 Red

CTA55 Green

CTA56 Blue

CCT INDIRECT

CTB00 Not required

CTB30 3000K

CTB35 3500K

CTB40 4000K

CTB54 Red

CTB55 Green

CTB56 Blue

F. UPLIGHT DIFFUSER

UD0 Not required

UD1 Clear diffuser

UD2 Opal diffuser ¹

¹ 10% reduction on indirect lumens.

G. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Available with DA01 dimming only.

³ Only available with DA45 dimming.

MACRO STRAIGHT™ - SUSPENDED

H. DIMMING

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1%¹

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

DA30 DSI/switchDim²

DA45 PoE³

¹ Not available with V3.

² Not available in North America.

³ Only available with V4.

I. FIXTURE FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA27 Wood grain - Light Cherry¹

FA28 Wood grain - Dark Walnut¹

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

¹ Longer lead time may apply, consult factory.

J. CANOPY FINISH

CF01 White

CF02 Black Metallic - Textured

CF20 Silver Metallic - Textured

CF25 Gold Metallic - Textured

CF44 Midnight Blue Metallic - Textured

CF45 Copper Metallic

CF46 Charcoal Metallic - Textured

CF47 Bronze Metallic - Textured

CF52 Champagne Metallic

CF53 Red Metallic - Textured

K. EMERGENCY

E0 Not required

E1 Emergency system - Integral¹

¹ Direct illumination and 120/277V or 240V only.

L. CIRCUITS

CS1 Single circuit

CS2 Dual circuit

M. CONTROLS

C0 Not required

C1 Encelium/Zigbee



MACRO STRAIGHT™ - SUSPENDED

DIMENSIONAL DIAGRAMS

