






MICRO CYLINDER 1.5

CLUSTER™


FULL SPECIFICATION SHEET



Fixture Type



Fixture Code




Quantities

1 DESCRIPTION

MICRO CYLINDER merges elegance with minimalism. The refined geometry and lustrous anodized bezels revamps a modest shape into a dashing pendant and complements exquisite interior designs. With lengths ranging from 12" to 36", **MICRO CYLINDER** lends itself to large-scale cascades without being obtrusive or overwhelming to a space. The light output is optimized according to the length of the cylinder allowing more lumen package options for various performance requirements. Regressed optics combined with bezels and a slender profile offer visual and aesthetic comfort. The minimalist form of **MICRO CYLINDER** blends into large spaces and creates a starlight effect when mounted at different levels. With a wide range of length options, this luminaire can be used as a primary source of light, while staggered arrangements add a sense of movement to the space.

2 OPTICS & FEATURES



3 APPROVALS



4 GENERAL SPECIFICATION**BODY**

Aluminum.

SUSPENSION/POWER CABLE

Power over aircraft cable.

DRIVER

Mounted in the canopy. HFP for 120-277V (EU-240V). The driver is integral to the fixture canopy.

DELIVERED LUMENS

Delivered lumens & LPW based on 4000K (min 90 CRI).

REPORTED L70 @25°C (77°F)

> 55,000 hrs

APPROVALS

Damp Rated.

FINISH

Powder coated.

BEZEL

Silver, black or gold anodized.

MECHANICAL

Mounts directly to or over an electrical junction box (by others - North America only).

SENSORS

Consult factory regarding sensor compatibility.

ESTIMATED L70 @25°C (77°F)

> 200,000 hrs

DESIGN

US Design Patent Pending.

5 DESIGN OPTIONS**Fixture Finish**


* Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.



MICRO CYLINDER 1.5 CLUSTER™ - SUSPENDED

FULL SPECIFICATION SHEET

CANOPY FINISH



BEZEL FINISH



6 HOW TO ORDER

1. LUMINAIRE

MCCL1P03 3 heads

MCCL1P05 5 heads

MCCL1P07 7 heads

* Data shown based on 42° beam angle. See performance data page in the download section for 25° beam angle. The data provided pertains to each head.

2. LENGTH OF HEADS

LOH12 12"

LOH18 18"

LOH24 24"

LOH36 36"

* If the heads need to be different lengths within a cluster, consult factory. The data provided pertains to each head.

3. CRI

CR90 CRI 90+

4. CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

5. BEAM ANGLE

BA25 25°

BA42 42°

6. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V

¹ Not available in North America.

7. DIMMING

DA01 0-10V Dimming 1.0%

8. FIXTURE FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA27 Wood grain - Light Cherry¹

FA28 Wood grain - Dark Walnut¹

FA30 Wood grain - White Oak¹

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

* Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

9. CANOPY FINISH

CF01 White

CF02 Black Metallic - Textured

CF20 Silver Metallic - Textured

CF25 Gold Metallic - Textured

CF44 Midnight Blue Metallic - Textured

CF45 Copper Metallic

CF46 Charcoal Metallic - Textured

CF47 Bronze Metallic - Textured

CF52 Champagne Metallic

CF53 Red Metallic - Textured

10. BEZEL FINISH

FB24 Black Anodized

FB58 Silver Anodized

FB59 Gold Anodized

11. SUSPENSION

HLA03 3ft cable suspension

HLA06 6ft cable suspension

HLA09 9ft cable suspension

* Custom lengths up to 20' are available, consult factory.



7 TECHNICAL DATA

LUMINAIRE

* Data shown based on 42° beam angle. See performance data page in the download section for 25° beam angle. The data provided pertains to each head.

Code	MCCL1P03	MCCL1P05	MCCL1P07
# of Heads	3	5	7

LENGTH OF HEADS

* If the heads need to be different lengths within a cluster, consult factory. The data provided pertains to each head.

Code	LOH12	LOH18	LOH24	LOH36
Length	12"	18"	24"	36"
Wattage	17	17	20	20
Delivered lms	800	800	900	900
LPW	45	45	44	44

8 PERFORMANCE DATA



BEAM 25°	LENGTH	DELIVERED LUMENS	WATTS / LPW	BEAM 42°		LENGTH	DELIVERED LUMENS	WATTS / LPW
				12"	18"			
	12"	700	17 / 43			12"	800	17 / 45
	18"	700	17 / 43			18"	800	17 / 45
	24"	800	20 / 42			24"	900	20 / 44
	36"	800	20 / 42			36"	900	20 / 44




MICRO CYLINDER 1.5 CLUSTER™ - SUSPENDED

FULL SPECIFICATION SHEET

9 DIMENSIONAL DIAGRAMS



ISOMETRIC TOP VIEW






ISOMETRIC BOTTOM VIEW






MICRO CYLINDER 1.5 CLUSTER™ - SUSPENDED

FULL SPECIFICATION SHEET



ISOMETRIC TOP VIEW

ISOMETRIC BOTTOM VIEW



ISOMETRIC TOP VIEW

ISOMETRIC BOTTOM VIEW