

MICRO CYLINDER 2.5™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MICRO CYLINDER 2.5™ - SUSPENDED



MICRO CYLINDER 2.5™ - SUSPENDED

Micro Cylinder dabs elegance to minimalism. Lustrous anodized bezels revamp a modest shape into a dashing pendant. With lengths ranging from 12" to 36", Micro Cylinder lends itself to large-scale cascades without being obtrusive or overwhelming to a space. The light output is optimized according to the length of the cylinder allowing more lumen package options for various performance requirements. Regressed optics combined with bezels and a slender profile offer visual and aesthetic comfort.

GENERAL SPECIFICATION

Body

Extruded aluminum.

Suspension/power cable

Power over aircraft cable.

Driver

HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture canopy.

Delivered lumens

Delivered lumens & LPW based on 4000K CRI 90+.

Reported L70 @25°C (77°F)

> 55,000 hrs

Approvals

Damp Rated.

Finish

Powder coated.

Bezel

Silver, black or gold anodized.

Mechanical

Luminaires mount directly over J box (by others).

Sensors

Consult factory regarding sensor compatibility.


Estimated L70 @25°C (77°F)

> 200,000 hrs

Design

US Design Patent Pending.

OPTICS & FEATURES



MICRO CYLINDER 2.5™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

MCYL2P12 12", 1700 lms	MCYL2P18 18", 1700 lms	MCYL2P24 24", 2200 lms	MCYL2P36 36", 2200 lms
-------------------------------	-------------------------------	-------------------------------	-------------------------------

Data shown based on 45° beam angle. See performance data page in the download section for 20° beam angle.

B. CRI

CR90 CRI 90+

C. CCT

CTA27 2700K	CTA30 3000K	CTA35 3500K	CTA40 4000K
--------------------	--------------------	--------------------	--------------------

D. BEAM ANGLE

BA20 20°	BA45 45°		
-----------------	-----------------	--	--

E. VOLTAGE

V1 120/277V	V2 240V ¹	V3 347V ²	
--------------------	-----------------------------	-----------------------------	--

¹ Not available in North America.
² Only available with DA01 dimming.

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0% ¹ DA30 DSL/switchDim ^{2 3}	DA02 0-10V Dimming 0.1% ²	DA20 DALI Dimming 0.1% ²	DA21 DALI Dimming 1.0% ²
---	---	--	--

¹ If V1 and DA01 are required in conjunction, the driver will be inside the junction box. For all other voltage and dimming options, the driver will be in a remote box.
² Not available with V3.
³ Not available in North America.

G. FIXTURE FINISH

FA01 White FA27 Wood grain - Light Cherry ¹ FA46 Charcoal Metallic - Textured	FA02 Black Metallic - Textured FA28 Wood grain - Dark Walnut ¹ FA47 Bronze Metallic - Textured	FA20 Silver Metallic - Textured FA44 Midnight Blue Metallic - Textured FA52 Champagne Metallic	FA25 Gold Metallic - Textured FA45 Copper Metallic FA53 Red Metallic - Textured
---	--	---	--

¹ Longer than normal lead times may apply, consult factory.

H. CANOPY FINISH

CF01 White CF44 Midnight Blue Metallic - Textured CF52 Champagne Metallic	CF02 Black Metallic - Textured CF45 Copper Metallic CF53 Red Metallic - Textured	CF20 Silver Metallic - Textured CF46 Charcoal Metallic - Textured	CF25 Gold Metallic - Textured CF47 Bronze Metallic - Textured
--	---	--	--

I. BEZEL FINISH

FB24 Black Anodized	FB58 Silver Anodized	FB59 Gold Anodized	
----------------------------	-----------------------------	---------------------------	--

J. SUSPENSION

HLA03 3ft cable suspension	HLA06 6ft cable suspension	HLA09 9ft cable suspension	
-----------------------------------	-----------------------------------	-----------------------------------	--

Custom lengths up to 20ft are available, consult factory.

MICRO CYLINDER 2.5™ - SUSPENDED













TECHNICAL DATA

LUMINAIRE

Data shown based on 45° beam angle. See performance data page in the download section for 20° beam angle.











Code	MCYL2P12	MCYL2P18	MCYL2P24	MCYL2P36
Length	12"	18"	24"	36"
Wattage	24	24	33	33
Delivered lms	1700	1700	2200	2200
LPW	69	69	66	66

FIXTURE FINISH

							
White	Black Metallic - Textured	Silver Metallic - Textured	Gold Metallic - Textured	Wood grain - Light Cherry¹	Wood grain - Dark Walnut¹	Midnight Blue Metallic - Textured	Copper Metallic
							
Charcoal Metallic - Textured	Bronze Metallic - Textured	Champagne Metallic	Red Metallic - Textured				

¹ Longer than normal lead times may apply, consult factory.

CANOPY FINISH

							
White	Black Metallic - Textured	Silver Metallic - Textured	Gold Metallic - Textured	Midnight Blue Metallic - Textured	Copper Metallic	Charcoal Metallic - Textured	Bronze Metallic - Textured
							
Champagne Metallic	Red Metallic - Textured						

MICRO CYLINDER 2.5™ - SUSPENDED

BEZEL FINISH



Black Anodized

Silver Anodized

Gold Anodized

APPROVALS



MICRO CYLINDER 2.5™ - SUSPENDED


PERFORMANCE DATA

BEAM 20°	LENGTH	DELIVERED LUMENS	WATTS / LPW
	12"	1700	24 / 69
	18"	1700	24 / 69
	24"	2200	33 / 66
	36"	2200	33 / 66

BEAM 45°	LENGTH	DELIVERED LUMENS	WATTS / LPW
	12"	1700	24 / 69
	18"	1700	24 / 69
	24"	2200	33 / 65
	36"	2200	33 / 65

MICRO CYLINDER 2.5™ - SUSPENDED

DIMENSIONAL DIAGRAMS



Fixture Length:	(A)
12" (MCYL2P12)	12" (304.8mm)
18" (MCYL2P18)	18" (457.2mm)
24" (MCYL2P24)	24" (609.6mm)
36" (MCYL2P36)	36" (914.4mm)