





# MICRO ELLIPSE II™


## FULL SPECIFICATION SHEET



Fixture Type



Fixture Code




Quantities


### 1 DESCRIPTION

No shape is more graceful than the ellipse. Featuring an ultra-sleek design with a 1" profile and lengths ranging from 3' to 6', **MICRO ELLIPSE II** is ideal for creating a lasting impression. Embellish a wall using multiple luminaires combined with a halo effect of indirect lighting. This dynamic shape offers direct or indirect light, providing versatility for unique illuminating effects. Boasting a high-efficiency, flexible lens that snugly fits the frame, **MICRO ELLIPSE II** eliminates any light leakage while ensuring a uniform and seamless diffusion of light. Whether used as a solitary statement piece or in a composition, **MICRO ELLIPSE II's** impact is undeniable, particularly notable for the ambient halo effect it casts with its indirect lighting. Moreover, **MICRO ELLIPSE II** addresses acoustic needs with an optional acoustic panel for sizes up to 4' in length. These panels are designed to reduce echo and reverberation commonly found in modern open-plan spaces, areas with exposed concrete, open ceilings, and large windows. For a touch of whimsy and creative flair, **MICRO ELLIPSE II** can be combined with other shapes like MICRO RING, MICRO TRIANGLE or MICRO QUAD, adding a dynamic and playful dimension to any space.


### 2 OPTICS & FEATURES




Ceiling Direct



Wall Direct



General Diffuse



Declare



PoE

### 3 APPROVALS

ADA



DAMP  
LOCATION



IP20



## 4 GENERAL SPECIFICATION

### BODY AND TRIM

Aluminium.

### LENS

Protruding Lens 0.08: (2.1mm).

### REMOTE EMERGENCY

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

### POE

Micro Ellipse II can integrate into your data network via Power over Ethernet (PoE) connectivity.

### REPORTED L70 @25°C(77°F)

> 60,000 hrs.

### FINISH

Powder coated.

### SENSORS

Consult factory regarding sensor compatibility.

### DRIVERS

Remote, HPF electronic drivers for 120-277V (EU-240V). Wire size 18 AWG - max distance (from fixture to drivers) 40' (12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation. For longer remote distances, consult factory.

### DELIVERED LUMENS

Delivered lumens & LPW based on 4000K (min 80 CRI).

### APPROVALS

Damp Rated.

## 5 DESIGN OPTIONS

### Fixture Finish



White

Black  
Metallic -  
Textured

Silver  
Metallic -  
Textured

Gold Metallic  
- Textured

Midnight  
Blue Metallic  
- Textured

Copper  
Metallic

Charcoal  
Metallic -  
Textured

Bronze  
Metallic -  
Textured



Champagne  
Metallic

**6 HOW TO ORDER****1. LUMINAIRE**

**METC1C03** 3ft, 2300 lms      **METC1C04** 4ft, 3200 lms      **METC1C05** 5ft, 4100 lms      **METC1C06** 6ft, 4800 lms

**2. LUMENS**

**LMA17** 175 lm/ft      **LMA26** 260 lm/ft      **LMA35** 350 lm/ft

<sup>1</sup> 50% of total output. <sup>2</sup> 75% of total output. <sup>3</sup> 100% total output.

**3. CRI**

**CR80** CRI 80+      **CR90** CRI 90+

**4. CCT**

**CTA27** 2700K      **CTA30** 3000K      **CTA35** 3500K      **CTA40** 4000K

**5. VOLTAGE**

**V1** 120/277V      **V2** 240V <sup>1</sup>      **V3** 347V <sup>2</sup>      **V4** Low Voltage <sup>3</sup>

<sup>1</sup> Not available in North America. <sup>2</sup> Available with DA01 dimming only. <sup>3</sup> Available with DA45 dimming only.

**6. DIMMING (REMOTE)**

**DA01** 0-10V Dimming 1.0%      **DA20** DALI Dimming 0.1% <sup>1</sup>      **DA21** DALI Dimming 1.0% <sup>1</sup>      **DA45** PoE <sup>2</sup>

<sup>1</sup> Not available with V3. <sup>2</sup> Available with V4 only.

**7. FIXTURE FINISH**

<b>FA01</b> White	<b>FA02</b> Black Metallic - Textured	<b>FA20</b> Silver Metallic - Textured	<b>FA25</b> Gold Metallic - Textured
<b>FA44</b> Midnight Blue Metallic - Textured	<b>FA45</b> Copper Metallic	<b>FA46</b> Charcoal Metallic - Textured	<b>FA47</b> Bronze Metallic - Textured
<b>FA52</b> Champagne Metallic			

**8. EMERGENCY**

**E0** Not required      **E2** Emergency system - Remote



7 PERFORMANCE DATA


<b>METC1C03</b> O/A Length x Width 36" x 16"	<b>Lumens</b>	<b>Watts</b>	<b>LPW</b>	<b>METC1C04</b> O/A Length x Width 48" x 19"	<b>Lumens</b>	<b>Watts</b>	<b>LPW</b>
LMA17	1100	17	68	LMA17	1600	23	68
LMA26	1700	25	68	LMA26	2400	35	68
LMA35	2300	35	67	LMA35	3200	48	67

<b>METC1C05</b> O/A Length x Width 60" x 22"	<b>Lumens</b>	<b>Watts</b>	<b>LPW</b>	<b>METC1C06</b> O/A Length x Width 72" x 25"	<b>Lumens</b>	<b>Watts</b>	<b>LPW</b>
LMA17	2100	30	69	LMA17	2400	35	69
LMA26	3100	45	68	LMA26	3600	53	68
LMA35	4100	61	67	LMA35	4800	71	67



8 DIMENSIONAL DIAGRAMS



**O/A Length X Width:**

914mm/36" X 406mm/16"

1219mm/48" X 483mm/19"

1524mm/60" X 559mm/22"

1829mm/72" X 635mm/25"