


MICRO ELLIPSE II™ - WALL OR CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MICRO ELLIPSE II™ - WALL OR CEILING SURFACE



# MICRO ELLIPSE II™ - WALL OR CEILING SURFACE

No shape is more graceful than the ellipse. With a super-slim 1" profile and lengths ranging from 3' to 6', **MICRO ELLIPSE II** is ideal for creating a lasting impression. Embellish a wall using multiple luminaires combined with a halo effect of indirect lighting.

## GENERAL SPECIFICATION

### Body and trim

Aluminium.

### Diffuser

Protruding Lens 0.08: (2.1mm).

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

### PoE

Micro Ellipse II can integrate into your data network via Power over Ethernet (PoE) connectivity.

### Reported L70 @25°C (77°F)

> 60,000 hrs.

### Finish

Powder coated.

### Sensors

Consult factory regarding sensor compatibility.

### Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V). Wire size 18 AWG - max distance (from fixture to drivers) 40' (12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation.

### Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).


### Approvals

Damp Rated.


## OPTICS & FEATURES



Ceiling Direct



Wall Direct



General Diffuse



Declare



PoE

# MICRO ELLIPSE II™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

<b>METC1C03</b> 3ft, 2300 lms	<b>METC1C04</b> 4ft, 3200 lms	<b>METC1C05</b> 5ft, 4100 lms	<b>METC1C06</b> 6ft, 4800 lms
-------------------------------	-------------------------------	-------------------------------	-------------------------------

### B. LUMENS

<b>LMA17</b> 175 lm/ft	<b>LMA26</b> 260 lm/ft	<b>LMA35</b> 350 lm/ft	
------------------------	------------------------	------------------------	--

<sup>1</sup> 50% of total output.  
<sup>2</sup> 75% of total output.  
<sup>3</sup> 100% total output.

### C. CRI

<b>CR80</b> CRI 80+	<b>CR90</b> CRI 90+		
---------------------	---------------------	--	--

### D. CCT

<b>CTA27</b> 2700K	<b>CTA30</b> 3000K	<b>CTA35</b> 3500K	<b>CTA40</b> 4000K
--------------------	--------------------	--------------------	--------------------

### E. VOLTAGE

<b>V1</b> 120/277V	<b>V2</b> 240V <sup>1</sup>	<b>V3</b> 347V <sup>2</sup>	<b>V4</b> Low Voltage <sup>3</sup>
--------------------	-----------------------------	-----------------------------	------------------------------------

<sup>1</sup> Not available in North America.  
<sup>2</sup> Available with DA01 dimming only.  
<sup>3</sup> Available with DA45 dimming only.

### F. DIMMING (REMOTE)

<b>DA01</b> 0-10V Dimming 1.0%	<b>DA20</b> DALI Dimming 0.1% <sup>1</sup>	<b>DA21</b> DALI Dimming 1.0% <sup>1</sup>	<b>DA45</b> PoE <sup>2</sup>
--------------------------------	--	--	------------------------------

<sup>1</sup> Not available with V3.  
<sup>2</sup> Available with V4 only.

### G. FIXTURE FINISH

<b>FA01</b> White	<b>FA02</b> Black Metallic - Textured	<b>FA20</b> Silver Metallic - Textured	<b>FA25</b> Gold Metallic - Textured
<b>FA44</b> Midnight Blue Metallic - Textured	<b>FA45</b> Copper Metallic	<b>FA46</b> Charcoal Metallic - Textured	<b>FA47</b> Bronze Metallic - Textured
<b>FA52</b> Champagne Metallic	<b>FA53</b> Red Metallic - Textured		

### H. EMERGENCY

<b>E0</b> Not required	<b>E2</b> Emergency system - Remote		
------------------------	-------------------------------------	--	--


# MICRO ELLIPSE II™ - WALL OR CEILING SURFACE

## TECHNICAL DATA


### LUMINAIRE

Code	METC1C03	METC1C04	METC1C05	METC1C06
Diameter (A)	3ft	4ft	5ft	6ft
O/A Width	16"	19"	22"	25"
Light Direction	Direct	Direct	Direct	Direct
Wattage	28W	39W	50W	58W
Delivered lms	2300	3200	4100	4800
LPW	82	83	83	83


### FIXTURE FINISH




White




Black Metallic -  
Textured




Silver Metallic -  
Textured




Gold Metallic -  
Textured




Midnight Blue Metallic -  
Textured




Copper Metallic




Charcoal Metallic -  
Textured



Bronze Metallic -  
Textured



Champagne Metallic



Red Metallic -  
Textured

### APPROVALS

ADA









DAMP  
LOCATION



IP20

MICRO ELLIPSE II™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS



- O/A Length X Width:**
- 914mm/36" X 406mm/16"
  - 1219mm/48" X 483mm/19"
  - 1524mm/60" X 559mm/22"
  - 1829mm/72" X 635mm/25"