






MICRO FLARE™


SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 HOW TO ORDER

1. LUMINAIRE

MFLR1P Direct

MFLR2P Direct/Indirect

All data based on max values, consult Performance Data download for more details. One power cord for every 50 linear feet.

2. LENGTH OF RUN

Order in 2' increments starting at 4'. For runs over 50' in length, consult factory.

SFA_ _ _ _

3. MAX LENGTH PER SECTION

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (3658mm) is selected, we would provide 4 3048mm segments. For special requirements, please contact sales@betacalco.com.

* Total length = length of run + 2.35in

4. LM/FT (DIRECT)

LPF010 100 lm/ft

LPF020 200 lm/ft

LPF030 300 lm/ft

LPF040 400 lm/ft

5. LM/FT (INDIRECT)

LPG000 Not required	LPG020 200 lm/ft	LPG040 400 lm/ft	LPG060 600 lm/ft
LPG080 800 lm/ft	LPG100 1000 lm/ft	LPG120 1200 lm/ft	LPG140 1400 lm/ft

6. CRI

CR90 CRI 90+

7. CCT

CTA27 2700K	CTA30 3000K	CTA35 3500K	CTA40 4000K
--------------------	--------------------	--------------------	--------------------

8. DIRECT LENS

DD3 Diffused Light

9. INDIRECT LENS

UD0 Not required	UD1 Clear (Batwing distribution)	UD3 Asymmetric ¹
-------------------------	---	------------------------------------

¹ Available up to 1000 lms/ft.

10. INDIRECT BLACKOUT PLATE

UB00 Not required	UB_ _ Blackout plate ¹
--------------------------	--

¹ Available on a per foot basis. May be required to prevent lighting up of duct work in loft style applications.

11. VOLTAGE

V1 120/277V	V2 240V ¹	V3 347V ²	V4 Low Voltage ³
--------------------	-----------------------------	-----------------------------	------------------------------------

¹ Not available in North America. ² Only available with DA01 dimming. ³ Only available with DA45 dimming.

12. DIMMING

DA01 0-10V Dimming 1.0%	DA02 0-10V Dimming 0.1% ¹	DA20 DALI Dimming 0.1% ¹	DA21 DALI Dimming 1.0% ¹
DA30 DSI/switchDim ²	DA45 PoE ³		

¹ Not available with V3. ² Not available in North America. ³ Only available with V4.

13. CEILING TYPE

G1 Grid ceiling ¹ **H1** Hard ceiling ²

¹ Combo kit includes installation to T-bar and through tile mount. ² Designed for drywall ceilings.

14. SUSPENSION

HLA03 3ft cable suspension **HLA06** 6ft cable suspension **HLA09** 9ft cable suspension

15. FIXTURE FINISH

FA01 White – Textured **FA02** Black Metallic – Textured **FA20** Silver Metallic – Textured **FA53** Red Metallic Textured

16. INSIDE TRIM FINISH

FB01 White **FB02** Black Metallic – Textured **FB20** Silver Metallic – Textured **FB25** Gold Metallic – Textured
FB53 Red Metallic – Textured

17. CANOPY FINISH

CF01 White **CF02** Black Metallic – Textured **CF20** Silver Metallic – Textured **CF53** Red Metallic Textured

18. EMERGENCY

E0 Not required **E2** Emergency system – Remote ¹ **E3** Emergency generated circuit ²

¹ Only available with 0-10V 1% dimming. An extra power cord will be supplied to each section of the fixture when ordering emergency.

² Available upon request, consult factory for details. Not available with 347V.

19. CIRCUITS

CS1 Single circuit **CS2** Dual circuit ¹

20. SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.