


MICRO RING DE™ - WALL OR CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MICRO RING DE™ - WALL OR CEILING SURFACE



# MICRO RING DE™ - WALL OR CEILING SURFACE

With a super slim profile and 5 diameters ranging from 26" to 72", **MICRO RING DE** is ideal for creating sizable cascaded circular arrangements on a ceiling or wall. The ring emits light from the inside and the outside of the ring, and can be coordinated with 4 other emission options in the MICRO RING family to create unique lighting effects. The buoyant and energetic nature of the ring makes **MICRO RING DE** just as impactful as a single standalone piece, especially when illuminated with color options, red, green, or blue. For a whimsical style, combine MICRO RING with MICRO TRIANGLE or MICRO QUAD.

## GENERAL SPECIFICATION

### Body and trim

Aluminium.

### Diffuser

Protruding Lens 0.08" (2.1mm).

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

### PoE

Integrates into your data network via Power over Ethernet (PoE) connectivity.

### Reported L70 @25°C (77°F)

> 60,000 hrs.

### Design

US Pat. No. D835,328.

### Finish

Powder coated.

### Sensors

Consult factory regarding sensor compatibility.

### Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V) dimming. Wire size 18 AWG - max distance (from fixture to drivers) 40' (12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation.

### Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI)

### Approvals

Damp Rated.

## OPTICS & FEATURES



Ceiling Inside/Outside

Wall Inside/Outside

General Diffuse

Declare

PoE

# MICRO RING DE™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

<b>MRHC2C02</b> 26", 2800 lms	<b>MRHC2C03</b> 36", 4000 lms	<b>MRHC2C04</b> 48", 5300 lms	<b>MRHC2C05</b> 60", 6800 lms
<b>MRHC2C06</b> 72", 8400 lms			

### B. LUMENS

<b>LPF027</b> 275 lms/ft <sup>1</sup>	<b>LPF041</b> 410 lms/ft <sup>2</sup>	<b>LPF055</b> 550 lms/ft <sup>3</sup>	
---------------------------------------	---------------------------------------	---------------------------------------	--

<sup>1</sup> Based on 50% of total output  
<sup>2</sup> Based on 75% of total output.  
<sup>3</sup> 100% of total output.

### C. CRI

<b>CR80</b> CRI 80+	<b>CR90</b> CRI 90+		
---------------------	---------------------	--	--

### D. CCT

<b>CTA27</b> 2700K	<b>CTA30</b> 3000K	<b>CTA35</b> 3500K	<b>CTA40</b> 4000K
--------------------	--------------------	--------------------	--------------------

### E. VOLTAGE

<b>V1</b> 120/277V	<b>V2</b> 240V <sup>1</sup>	<b>V3</b> 347V <sup>2</sup>	<b>V4</b> Low Voltage <sup>3</sup>
--------------------	-----------------------------	-----------------------------	------------------------------------

<sup>1</sup> Not available in North America.  
<sup>2</sup> Available with DA01 dimming only.  
<sup>3</sup> Available with DA45 dimming only.

### F. DIMMING (REMOTE)

<b>DA01</b> 0-10V Dimming 1.0%	<b>DA20</b> DALI Dimming 0.1% <sup>1</sup>	<b>DA21</b> DALI Dimming 1.0% <sup>1</sup>	<b>DA45</b> PoE <sup>2</sup>
--------------------------------	--	--	------------------------------

<sup>1</sup> Not available with V3.  
<sup>2</sup> Available with V4 only.

### G. FINISH

<b>FA01</b> White	<b>FA02</b> Black Metallic - Textured	<b>FA20</b> Silver Metallic - Textured	<b>FA25</b> Gold Metallic - Textured
<b>FA44</b> Midnight Blue Metallic - Textured	<b>FA45</b> Copper Metallic	<b>FA46</b> Charcoal Metallic - Textured	<b>FA47</b> Bronze Metallic - Textured
<b>FA52</b> Champagne Metallic	<b>FA53</b> Red Metallic - Textured		

### H. EMERGENCY

<b>E0</b> Not required	<b>E2</b> Emergency system - Remote		
------------------------	-------------------------------------	--	--

### I. SURFACE MOUNTING KITS

<b>MK1</b> Surface mounting kit 1.25" extension c/w 3 spacers <sup>1</sup>	<b>ML1</b> Surface mounting kit 2.75" extension c/w 3 spacers <sup>2</sup>	<b>MK2</b> Surface mounting kit 1.25" extension c/w 4 spacers <sup>1 3</sup>	<b>ML2</b> Surface mounting kit 2.75" extension c/w 4 spacers <sup>2 3</sup>
--	--	--	--

<sup>1</sup> Comes standard.  
<sup>2</sup> Extended length optional.  
<sup>3</sup> For use with MREC2C06 only.


# MICRO RING DE™ - WALL OR CEILING SURFACE

## TECHNICAL DATA


### LUMINAIRE

Code	MRHC2C02	MRHC2C03	MRHC2C04	MRHC2C05	MRHC2C06
Diameter (A)	26"	36"	48"	60"	72"
Wattage	46W	66W	87W	111W	137W
Delivered lms	2800	4000	5300	6800	8400
LPW	61	61	61	61	61
Mounting Points	3	3	3	3	4


### FINISH




White




Black Metallic -  
Textured




Silver Metallic -  
Textured




Gold Metallic -  
Textured




Midnight Blue Metallic -  
Textured




Copper Metallic




Charcoal Metallic -  
Textured



Bronze Metallic -  
Textured



Champagne Metallic



Red Metallic -  
Textured

### APPROVALS

ADA







DAMP  
LOCATION



IP20

# MICRO RING DE™ - WALL OR CEILING SURFACE

## DIMENSIONAL DIAGRAMS

