


MICRO RING DE™ - WALL OR CEILING SURFACE



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

MRHC2C02 26", 2800 lms
MRHC2C06 72", 8400 lms

MRHC2C03 36", 4000 lms

MRHC2C04 48", 5300 lms

MRHC2C05 60", 6800 lms

B. LUMENS

LPF027 275 lms/ft¹

LPF041 410 lms/ft²

LPF055 550 lms/ft³

¹ Based on 50% of total output

² Based on 75% of total output.

³ 100% of total output.

C. CRI

CR80 CRI 80+

CR90 CRI 90+

D. CCT

CTA27 2700K¹

CTA30 3000K

CTA35 3500K

CTA40 4000K

E. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V²

V4 Low Voltage³

¹ Not available in North America.

² Available with DA01 dimming only.

³ Available with DA45 dimming only.

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

DA45 PoE²

¹ Not available with V3.

² Available with V4 only.

G. FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

H. EMERGENCY

E0 Not required

E2 Emergency system - Remote

I. SURFACE MOUNTING KITS

MK1 Surface mounting kit 1.25" extension c/w 3 spacers¹

ML1 Surface mounting kit 2.75" extension c/w 3 spacers²

MK2 Surface mounting kit 1.25" extension c/w 4 spacers^{1 3}

ML2 Surface mounting kit 2.75" extension c/w 4 spacers^{2 3}

¹ Comes standard.

² Extended length optional.

³ For use with MREC2C06 only.



MICRO RING DE™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

