

MICRO RING II™ - VERTICAL SUSPENDED

Project Name:




Fixture Type:

Fixture Code:

Quantities:



MICRO RING II™ - VERTICAL SUSPENDED



MICRO RING II™ - VERTICAL SUSPENDED

MICRO RING II VERTICAL reimagines the classic ring design with its vertical orientation, creating an exquisite pendant that radiates enduring elegance. Reminiscent of an era when graceful, suspended jewelry adorned the most refined occasions, its sleek and slender profile is ideal for creating a captivating clustering and cascading effect when multiple pendants are arranged together. This design element adds an intriguing dynamic to your space, enhancing its visual appeal and creating a captivating focal point. **MICRO RING II VERTICAL** sets a new performance benchmark in decorative rings, boasting a best-in-class lumen efficacy of 105 LPW. This performance is not just about brightness but about the quality of light. Its high-efficiency, flexible diffuser snugly fits the frame, eliminating any light leakage. The result is a uniform and seamless diffusion of light that enhances the overall aesthetic of your space.

Expanding your options to better meet a wide range of design requirements, we now offer a lower output **MICRO RING II VERTICAL**. This new addition is designed to serve your decorative needs where subtler, more atmospheric lighting is desired without compromising on the quality and uniformity of light diffusion that the **MICRO RING II VERTICAL** is celebrated for. Ideal for creating ambient moods in intimate settings or when a less pronounced lighting effect is required, this lower output option expands the versatility of the MICRO RING collection, ensuring that there is a ring solution for every design challenge.

GENERAL SPECIFICATION

Body

Aluminum.

Power cable

Silver braided.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

PoE

Micro Ring II can integrate into your data network via Power over Ethernet (PoE) connectivity.

Mechanical

Luminaires mount directly over J box (by others - North America only).

L70 @25°C

> 60,000 hrs.

Approvals

Damp Rated.

Finish

Powder coated

Diffuser

Protruding Lens 0.08" (2.1mm)

Drivers

Remote, HPF electronic drivers for 120-277V, 347V (EU-240V) dimming. Wire size 18 AWG - max distance (from fixture to drivers) 40' (12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation. Drivers are either remote mounted or integral to the canopy depending on the size of the fixture.

Suspension

Steel cables (SS1, SS3) and Power Over Suspension (SS6).


Sensors

Consult factory regarding sensor compatibility.

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

MOUNTING & OPTICS



Suspended Front/Back



Declare



PoE



MICRO RING II™ - VERTICAL SUSPENDED

HOW TO ORDER

A. LUMINAIRE

MRTV2P02 2ft Direct/Indirect, 6800
lms

MRTV2P03 3ft Direct/Indirect, 10200
lms

MRTV2P04 4ft Direct/Indirect, 13800
lms

MRTV2P05 5ft Direct/Indirect, 17300
lms

MRTV2P06 6ft Direct/Indirect, 20400
lms

B. EFFICIENCY

EFF1 Standard efficiency ¹

EFF2 High efficiency ²

¹ Standard efficiency refers to Standard efficacy.

² High efficiency refers to High efficacy. This option is 52% more efficient than Standard efficiency.

C. LUMENS/FT

LPF017 175 lm/ft ^{1 2}

LPF026 260 lm/ft ^{1 2}

LPF035 350 lm/ft ^{1 2}

LPF052 525 lm/ft ²

¹ Standard efficiency is available from 175 lm/ft to 350 lm/ft.

² High efficiency is available from 175 lm/ft to 525 lm/ft.

D. CRI

CR80 CRI 80+

CR90 CRI 90+

E. CCT

CTA27 2700K ¹

CTA30 3000K

CTA35 3500K

CTA40 4000K

¹ Longer than normal lead times may apply, consult factory for details.

F. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Available with DA01 dimming only.

³ V4 available with DA45 dimming only.

G. DIMMING

DA01 0-10V Dimming 1.0%

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% ¹

DA45 PoE ²

¹ Not available with MRTV2P05 or MRTV2P06.

² Available with V4 only.

H. SUSPENSION

SS1 Vertical, Remote driver

SS3 Vertical, Driver Integral to Canopy ¹

SS6 Power Over Suspension, Vertical
Remote driver ²

¹ Available up to 4ft diameter when using DALI dimming (DA20 & DA21).

² Available up to 5ft diameter when using DA01 and up to 4ft diameter when using DA20 or DA21.



MICRO RING II™ - VERTICAL SUSPENDED

I. FIXTURE FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry ¹	FA28 Wood grain - Dark Walnut ¹	FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic
FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic	FA53 Red Metallic - Textured

¹ Wood grain finishes are not available for the 2ft diameter.
Longer than normal lead times may apply, consult factory.

J. CANOPY FINISH

CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured	CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured	CF47 Bronze Metallic - Textured
CF52 Champagne Metallic	CF53 Red Metallic - Textured		

K. EMERGENCY

E0 Not required	E2 Emergency system - Remote
------------------------	-------------------------------------


MICRO RING II™ - VERTICAL SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	MRTV2P02	MRTV2P03	MRTV2P04	MRTV2P05	MRTV2P06
Diameter (A)	2ft	3ft	4ft	5ft	6ft
Light Direction	Front/Back	Front/Back	Front/Back	Front/Back	Front/Back
Stan. Eff. Watts Max	69	103	138	168	205
Stan. Eff. Del. Lms Max	4500	6600	9100	11300	13300
Stan. Eff. LPW Max	69	69	69	69	69
High Eff. Watts Max	68	102	136	171	202
High Eff. Del. Lms Max	6800	10200	13800	17300	20400
High Eff. LPW Max	105	105	105	105	105
Suspension Points	2	2	2	2	2
# of Sections and Canopies	1	1	1	1	1

FIXTURE FINISH




¹ Wood grain finishes are not available for the 2ft diameter.
Longer than normal lead times may apply, consult factory.

MICRO RING II™ - VERTICAL SUSPENDED


CANOPY FINISH



White



Black Metallic -
Textured




Silver Metallic -
Textured




Gold Metallic -
Textured



Midnight Blue Metallic -
Textured



Copper Metallic



Charcoal Metallic -
Textured



Bronze Metallic -
Textured



Champagne Metallic



Red Metallic -
Textured

APPROVALS



DAMP
LOCATION




IP20


MICRO RING II™ - VERTICAL SUSPENDED

DIMENSIONAL DIAGRAMS

SS1 VERTICAL - REMOTE DRIVER



SS3 VERTICAL - INTEGRAL DRIVER



SS6 VERTICAL - REMOTE DRIVER

